Advance TBR Size and Availability Chart

SIZE \ PATTERN	GL256F	GL215A	GL225A	GL257A	GL258A	GL274A	GL276A	GL282A	GL283A	GL283A LET	GL286A	GL288A	GL291A	GL296A	GL216D	GL226D	GL266D	GL266D ULT
8.25R15																		
6.50R16																		
7.00R16									●									
7.50R16									●									
8.25R16									●									
235/85R16																		
7.00R20									●									
7.50R20									●									
8.25R20						●			●									
9.00R20						●			●									
10.00R20						●	●		●			●						
11.00R20						●		●	●			●						
12.00R20						●			●			●	●					
12.00R24													●					
14.00R20																		
15.5R20																		
16.00R20																		
335/80R20																		
395/85R20																		
9.5R17.5									●									
10R17.5									●									
8R19.5									●									
9R22.5						●			●									
10R22.5						●			●									
11R22.5		●	●			●	●	●	●	●		●			●	●	●	●
11R24.5								●	●	●							●	●
12R22.5		●	●		●	●		●	●			●			●	●		
13R22.5									●			●						
215/75R17.5									●									
235/75R17.5									●									
225/70R19.5									●									
245/70R19.5									●									
265/70R19.5									●									
255/70R22.5									●									
275/70R22.5									●									
315/70R22.5								●										
295/75R22.5								●	●	●							●	●
285/75R24.5								●	●	●							●	●
275/80R22.5									●									
295/80R22.5				●										●				
315/80R22.5								●						●				
385/65R22.5	●																	
425/65R22.5											●							
445/65R22.5																		

NOTE: L.E..T.-Low Emission Technology
ULT-Ultra Design

2013前进外贸轮胎-内页-ok.indd 1 2013-9-17 17:07:22

RADIAL TRUCK TYRES

Advance TBR Size and Availability Chart

SIZE \ PATTERN	GL267D	GL268D	GL275D	GL293D	GL293D ULT	GL250T	GL260T	GL283T	GL285T	GL286T	GL298T	GL299T	GL659A	GL662A	GL665A	GL671A	GL679A	GL682A
8.25R15																		
6.50R16																●		
7.00R16																●		
7.50R16																●	●	
8.25R16																●	●	
235/85R16									●									
7.00R20																		
7.50R20																●		
8.25R20																●		
9.00R20																●		
10.00R20		●											●	●		●		
11.00R20		●		●								●				●		●
12.00R20		●		●							●		●			●		●
12.00R24															●			
14.00R20																		
15.5R20																		
16.00R20																		
335/80R20																		
395/85R20																		
9.5R17.5																		
10R17.5																		
8R19.5																		
9R22.5																		
10R22.5																		
11R22.5		●	●	●	●				●					●	●	●		
11R24.5		●		●	●				●					●		●		
12R22.5	●	●		●									●	●	●	●		
13R22.5		●											●	●	●	●		
215/75R17.5								●										
235/75R17.5								●										
225/70R19.5		●																
245/70R19.5		●																
265/70R19.5																		
255/70R22.5																		
275/70R22.5																		
315/70R22.5	●																	
295/75R22.5		●		●	●				●					●				
285/75R24.5		●		●	●				●					●				
275/80R22.5																		
295/80R22.5	●	●												●	●			
315/80R22.5	●	●												●	●			
385/65R22.5						●				●								
425/65R22.5										●								
445/65R22.5																		

NOTE: L.E..T.-Low Emission Technology
ULT-Ultra Design

2013前进外贸轮胎-内页-ok.indd 2 2013-9-17 17:07:26

Advance TBR Size and Availability Chart

SIZE \ PATTERN	GL689A	GL691A	GL697A	GL656D	GL663D	GL672D	GL681D	GL687D	GL670T	GL908A	GL909A	GL912A	GL918A	GL969A	GL992A	GL828A	GL073A	GL718D
8.25R15																		
6.50R16																		
7.00R16					●	●												
7.50R16	●		●		●	●				●								
8.25R16	●		●		●	●				●								
235/85R16																		
7.00R20																		
7.50R20																		
8.25R20			●		●	●				●								
9.00R20	●				●	●	●	●		●				●				
10.00R20	●				●	●	●	●		●				●	●			
11.00R20	●		●		●	●	●	●		●	●	●	●	●	●			
12.00R20	●		●		●		●	●		●		●	●	●	●		●	
12.00R24		●									●							
14.00R20																	●	
15.5R20																	●	
16.00R20																	●	
335/80R20																	●	
395/85R20																	●	
9.5R17.5																		
10R17.5																		
8R19.5																		
9R22.5																		
10R22.5																		
11R22.5				●							●				●	●		
11R24.5				●							●							
12R22.5								●			●				●			
13R22.5					●			●							●			
215/75R17.5																		
235/75R17.5																		
225/70R19.5																		
245/70R19.5																		
265/70R19.5																		
255/70R22.5																		
275/70R22.5																		
315/70R22.5																		
295/75R22.5																		
285/75R24.5																		
275/80R22.5																●		
295/80R22.5										●								●
315/80R22.5								●										
385/65R22.5	●								●									
425/65R22.5	●								●									
445/65R22.5	●								●									

NOTE: L.E..T.-Low Emission Technology
ULT-Ultra Design

2013前进外贸轮胎-内页-ok.indd 3 2013-9-17 17:07:27

Advance TBR Application Chart

	Long Haul Highway Service	Reginal Highway Service	On & Off Road Service	Off Road Service	Special Service
Steer	GL115S GL116S	GL256F			
All-Position		GL215A GL225A GL257A GL258A GL274A GL276A GL281A GL282A GL283A GL283A LET GL286A GL288A GL291A GL296A	GL659A GL662A GL665A GL671A GL679A GL682A GL689A GL691A GL697A	GL908A GL909A GL912A GL918A GL969A GL992A	GL828A GL073A
Drive	GL160D	GL216D GL226D GL261D GL265D GL266D GL266D ULT GL267D GL268D GL275D GL293D GL293D ULT	GL656D GL663D GL672D GL681D GL687D		GL718D
Trailer	GL155T	GL250T GL251T GL252T GL253T GL260T GL283T GL285T GL286T GL298T GL299T	GL670T		

● GL115S GL116S GL160D GL155T GL261D GL281A are developing

TREAD PATTERN DESIGNATIONS

Advance uses specific names,numbers,or letters to identify different types of tread patterns,benefits.

GL	2	83	A	L.E.T
ADVANCE Radial	Application	Serial Number	Position	Benefit

For example:

Advance Radial	GL=Advance Radial
Application	1 = Long Haul Highway Service
	2 = Reginal Highway Service
	6 = On & Off Road Service
	8 = City Buses Service
	9 = Off Road Service
	0 = Special Service
Position	S = Steer
	A = All-Position
	D = Drive
	T = Trailer
Benefit	L.E.T. = Low Emission Technology
	ULT = Ultra Design

2013前进外贸轮胎-内页-ok.indd 4 2013-9-17 17:07:28

Radial Truck Tyre Contents

GL256F Regional Highway Steer-Position 7
GL215A Regional Highway All-Position 8
GL225A Regional Highway All-Position 9
GL257A Regional Highway All-Position 10
GL258A Regional Highway All-Position 11
GL274A Regional Highway All-Position 12
GL276A Regional Highway All-Position 13
GL282A Regional Highway All-Position 14
GL283A Regional Highway All-Position 15-16
GL283A **L.E.T** Regional Highway All-Position 17
GL286A Regional Highway All-Position 18
GL288A Regional Highway All-Position 19
GL291A Regional Highway All-Position 20
GL296A Regional Highway All-Position 21
GL216D Regional Highway Drive-Position 22
GL226D Regional Highway Drive-Position 23
GL266D Regional Highway Drive-Position 24
GL226D **ULT** Regional Highway Drive-Position 25
GL267D Regional Highway Drive-Position 26
GL268D Regional Highway Drive-Position 27
GL275D Regional Highway Drive-Position 28
GL293D Regional Highway Drive-Position 29
GL293D **L.E.T** Regional Highway Drive-Position 30
GL293D **ULT** Regional Highway Drive-Position 31
GL250T Regional Highway Trailer-Position 32
GL260T Regional Highway Trailer-Position 33
GL283T Regional Highway Trailer-Position 34

2013前进外贸轮胎-内页-ok.indd 5 2013-9-17 17:07:28

GL285T Regional Highway Trailer-Position 35
GL286T Regional Highway Trailer-Position 36
GL298T Regional Highway Trailer-Position 37
GL299T Regional Highway Trailer-Position 38
GL659A On & Off Road All-Position 39
GL662A On & Off Road All-Position 40
GL665A On & Off Road All-Position 41
GL671A On & Off Road All-Position 42
GL679A On & Off Road All-Position 43
GL682A On & Off Road All-Position 44
GL689A On & Off Road All-Position 45
GL691A On & Off Road All-Position 46
GL697A On & Off Road All-Position 47
GL656D On & Off Road Drive-Position 48
GL663D On & Off Road Drive-Position 49
GL672D On & Off Road Drive-Position 50
GL681D On & Off Road Drive-Position 51
GL687D On & Off Road Drive-Position 52
GL670T On & Off Road Trailer-Position 53
GL718D Severe Snow Condition Drive-Position 54
GL828A City buses All-Position 55
GL908A Off Road All-Position 56
GL909A Off Road All-Position 57
GL912A Off Road All-Position 58
GL918A Off Road All-Position 59
GL969A Off Road All-Position 60
GL992A Off Road All-Position 61
GL073A Military Service All-Position 62

2013前进外贸轮胎-内页-ok.indd 6 2013-9-17 17:07:28

GL256F Regional Highway Steer-Position Radial

Product Features

- Optimized profile designing makes a tire has better abrasion resistance and better operational property.
- Excellent recipe makes a tire has superstrong abrasion resistance.
- Optimized crown designing makes a tire has good puncture resistance and better durability.
- Strengthened carcass designing makes a tire has longer service life and can be retreaded several times.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB635	A1ABB386	^{E}385/65R22.5^{S}	18	158	L	TL	GL256F	389	15.3	1072	42.2	850	125	S4250	S9370	11.75		15.5	19.5			
13GBB638	A1ABB389	^{E}385/65R22.5^{S}	20	160	K	TL	GL256F	389	15.3	1072	42.2	900	130	S4500	S9920	11.75		15.5	19.5			

2013前进外贸轮胎-内页-ok.indd 7 2013-9-17 17:07:29

GL215A Regional Highway All-Position Radial

Product Features

- Wider crown design,better operational stability of tire.
- Completely new recipe design, exceptional resistance to wear.
- Deeper pattern, longer service life of tire.
- Completely new protection design of groove bottom, largely strengthens resistance to puncture,and effectively improves resistance to crown blowout.
- Improved chafer design reflects an excellent bead endurance.
- Optimized groove design gurantees a tire's wet skid resistance.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
TBA	TBA	11R22.5	14	S144/ D142	M	TL	GL215A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	15.0	18.9			
13GBB785	A1ABB515	11R22.5	16	S146/ D143	M	TL	GL215A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	15.0	18.9			
13GBB786	A1ABB516	11R22.5	18	S148/ D145	L	TL	GL215A	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	15.0	18.9			
13GBB713	A1ABB469	12R22.5	16	S150/ D146	M	TL	GL215A	300	11.8	1084	42.7	800	115	S3350/ D3000	S7390/ D6610	9.00	DR08	15.0	18.9			
13GBB775	11ABB448	12R22.5	18	S152/ D148	L	TL	GL215A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	15.0	18.9			

2013前进外贸轮胎-内页-ok.indd 8 2013-9-17 17:07:30

GL225A Regional Highway All-Position Radial

Product Features

- Wider crown makes a tire has better operational stability.
- Completely new recipe designing makes a tire has superstrong abrasion resistance.
- Wider tread pattern makes a tire service longer.
- Completely new designing of groove bottom protection largely strengthens puncture resistance and effectively improves the properties of crown blowout.
- Modified chafter designing reflects an excellent bead durability property.
- Optimized groove designing gurantees a tire's wet skid resistance.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
TBA	TBA	11R22.5	14	S144/ D142	M	TL	GL225A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	15.0	18.9			
13GBB796	TBA	11R22.5	16	S146/ D143	M	TL	GL225A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	15.0	18.9			
13GBB797	TBA	11R22.5	18	S148/ D145	L	TL	GL225A	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	15.0	18.9			
13GBB737	A1ABB492	12R22.5	16	S150/ D146	M	TL	GL225A	300	11.8	1084	42.7	800	115	S3350/ D3000	S7390/ D6610	9.00	DR08	15.0	18.9			
13GBB777	11ABB450	12R22.5	18	S152/ D148	L	TL	GL225A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	15.0	18.9			

2013前进外贸轮胎-内页-ok.indd 9 2013-9-17 17:07:31

GL257A Regional Highway All-Position Radial

Product Features

- Self-clean technology of the groove and extra deep undertread designing makes a tire have excellent self-clean property and puncture resistance, so as to provide optimum safety guarantee for a tire.
- Optimized groove shape designing makes a tire have more excellent water resistance and wet skid resistance.
- Extra deep pattern can get longer service life.
- Thicken the sidewall designing can effectively protect the sidewall from scaping,so as to provide sidewall optimum protection.
- The use of special tread recipe makes rolling resistance lower and fuel consumption lower.
- Superstrong chafer with design patent provides a tire optimum carrying capacity and resistance to failure.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB578	11ABB346	E 295/80R22.5	16	S150/ D146	M	TL	GL257A	298	11.7	1044	41.1	800	115	S3350/ D3000	S7390/ D6610	9.00	DR08	16.0	20.2			
TBA	TBA	E 295/80R22.5	18	S152/ D148	L	TL	GL257A	298	11.7	1044	41.1	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	16.0	20.2			

2013前进外贸轮胎-内页-ok.indd 10 2013-9-17 17:07:36

GL258A Regional Highway All-Position Radial

Product Features

- Extra wide tread designing effectively improves the abrasion resistance of a tire.
- Outstanding stability and riding comfort under highway condition.
- Overlong service life.
- Excellent low fuel consumption.
- High-level carcass durability.
- Unique crown arc and groove designing provides excellent irregular abrasion resistance and stone inserting resistance.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB576	11ABB348	E 12R22.5	16	S150/ D147	M	TL	GL258A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	16.0	20.2			
TBA	TBA	E 12R22.5	18	S152/ D148	L	TL	GL258A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	16.0	20.2			

2013前进外贸轮胎-内页-ok.indd 11 2013-9-17 17:07:38

RADIAL TRUCK TYRES

GL274A Regional Highway All-Position Radial

Product Features

- Optimized belt structure strengthens the rigidity and flex at crown area which can guarantee the uniform wear of a tire.
- Four ""Z"" circumferential grooves at center makes a tire have excellent operational property.
- Completely new concept of tread cap recipe designing guarantees excellent abrasion property.
- Lateral small grooves at the patterns of both sides can strengthen traction at wet road surface.
- Reasonable pattern shape designing and contact shape can guarantee the uniform wear of a tire.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB348	11ABB140	E 8.25R20 S	14	S136/ D134	K	TT	GL274A	236	9.3	974	38.3	830	120	S2240/ D2120	S4940/ D4675	6.50	DG06C	14.0	17.6			
13GBB425	11ABB257	E 8.25R20 S	16	S139/ D137	J	TT	GL274A	236	9.3	974	38.3	930	135	S2430/ D2300	S5355/ D5070	6.50	DG06C	14.0	17.6			
13GBB350	11ABB142	E 9.00R20 S	16	S144/ D142	K	TT	GL274A	259	10.2	1019	40.1	900	130	S2800/ D2650	S6175/ D5840	7.00	DG07C	14.0	17.6			
13GBB533	11ABB312	E 10.00R20 S	16	S146/ D143	K	TT	GL274A	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	14.5	18.3			
13GBB340	11ABB132	E 10.00R20 S	18	S149/ D146	J	TT	GL274A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	14.5	18.3			
13GBB456	11ABB280	E 11.00R20 S	16	S150/ D147	K	TT	GL274A	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	15.0	18.9			
13GBB341	11ABB133	E 11.00R20 S	18	S152/ D149	J	TT	GL274A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	15.0	18.9			
13GBB169	11ABB076	12.00R20	16	S152/ D149	K	TT	GL274A	313	12.3	1122	44.2	760	110	S3550/ D3250	S7830/ D7160	8.50	DG09C	16.0	20.2			
13GBB662	11ABB405	E 12.00R20 S	18	S154/ D151	K	TT	GL274A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	16.0	20.2			
TBA	TBA	E 12.00R20 S	20	S156/ D153	J	TT	GL274A	313	12.3	1122	44.2	900	130	S4000/ D3650	S8820/ D8050	8.50	DG09C	16.0	20.2			
TBA	TBA	E 9R22.5 S	12	S133/ D131	M	TL	GL274A	229	9.0	974	38.3	675	95	S2060/ D1950	S4540/ D4300	6.75	DR06	14.0	17.6			
13GBB275	A1ABB211	E 9R22.5 S	14	S136/ D134	M	TL	GL274A	229	9.0	974	38.3	830	120	S2240/ D2120	S4940/ D4675	6.75	DR06	14.0	17.6			
13GBB210	A1ABB146	E 10R22.5 S	14	S141/ D139	M	TL	GL274A	254	10.0	1020	40.2	790	115	S2575/ D2430	S5675/ D5355	7.50	DR06	14.5	18.3			
TBA	TBA	E 10R22.5 S	16	S144/ D142	L	TL	GL274A	254	10.0	1020	40.2	850	125	S2800/ D2650	S6175/ D5840	7.50	DR06	14.5	18.3			
13GBB204	A1ABB140	11R22.5	14	S144/ D142	M	TL	GL274A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	14.5	18.3			
13GBB205	A1ABB141	E 11R22.5 S	16	S146/ D143	M	TL	GL274A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	14.5	18.3			
13GBB234	A1ABB170	E 12R22.5 S	16	S150/ D147	M	TL	GL274A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	15.5	19.5			
TBA	A1ABB475	E 12R22.5 S	18	S152/ D148	L	TL	GL274A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	15.0	18.9			

2013前进外贸轮胎-内页-ok.indd 12 2013-9-17 17:07:39

GL276A Regional Highway All-Position Radial

Product Features

- Optimized belt structure strengthens the rigidity and flex at crown area which can guarantee the uniform wear of a tire.
- Optimized four circumferential grooves at center makes a tire have better operational property when the tire is running.
- Small and narrow lateral patterns connecting at central four circumferential grooves makes a tire have better water resistance, stronger traction and wet skid resistance.
- Small and narrow grooves at both sides guarantee uniform tire wear, which reduces irregular wear.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB157	11ABB077	[E] 10.00R20	16	S146/ D143	K	TT	GL276A	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	14.5	18.3			
13GBB339	11ABB131	[E] 10.00R20	18	S149/ D146	J	TT	GL276A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	14.5	18.3			
13GBB214	A1ABB150	11R22.5	14	S144/ D142	M	TL	GL276A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	15.0	18.9			
13GBB221	A1ABB157	[E] 11R22.5	16	S146/ D143	M	TL	GL276A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	15.0	18.9			
TBA	TBA	[E] 11R22.5	18	S148/ D145	L	TL	GL276A	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	15.0	18.9			

2013前进外贸轮胎-内页-ok.indd 13 2013-9-17 17:07:40

GL282A Regional Highway All-Position Radial

Product Features

- Completely optimized structure and recipe designing makes a tire has better cost performance ratio.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.
- Optimized shoulder profile designing makes a tire have better heat dispersion and higher crown durability.
- Completely new crown designing largely strengthens a tire's puncture resistance and effectively improve a tire's safety.
- Optimized groove designing guarantees a tire's wet skid resistance.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB790	A1ABB522	11.00R20	18	S152/ D149	J	TT	GL282A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	15.0	18.9			
13GBB652	A1ABB408	11R22.5	14	S144/ D142	M	TL	GL282A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	13.9	17.5			
13GBB653	A1ABB410	E 11R22.5 SL	16	S146/ D143	M	TL	GL282A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	13.9	17.5	D	B	74
13GBB743	A1ABB497	E 11R22.5 SL	18	S148/ D145	L	TL	GL282A	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	13.9	17.5	D	B	74
13GBB654	A1ABB412	E 11R24.5	14	S146/ D143	M	TL	GL282A	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	14.0	17.6			
13GBB655	A1ABB413	E 11R24.5	16	S149/ D146	L	TL	GL282A	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	14.0	17.6			
13GBB771	11ABB443	E 12R22.5 SL	16	S150/ D147	M	TL	GL282A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	15.0	18.9	D	C	75
TBA	TBA	E 12R22.5 SL	18	S152/ D148	L	TL	GL282A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	15.0	18.9	D	C	75
13GBB658	A1ABB416	285/75R24.5	14	S144/ D141	M	TL	GL282A	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	14.0	17.6			
13GBB659	A1ABB417	285/75R24.5	16	S147/ D144	L	TL	GL282A	283	11.1	1050	41.3	830	120	S3075/ D2800	S6780/ D6175	8.25	DR07	14.0	17.6			
13GBB660	A1ABB418	295/75R22.5	14	S144/ D141	M	TL	GL282A	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	14.0	17.6			
13GBB66	A1ABB420	295/75R22.5	16	S146/ D143	L	TL	GL282A	298	11.7	1014	39.9	830	120	S3000/ D2725	S6610/ D6005	9.00	DR08	14.0	17.6			
13GBB695	A1ABB449	E 295/80R22.5 SL	16	S150/ D146	M	TL	GL282A	298	11.7	1044	41.1	800	115	S3350/ D3150	S7390/ D6610	9.00	DR08	14.8	18.6	D	B	75
13GBB739	A1ABB404	E 295/80R22.5 SL	18	S152/ D148	L	TL	GL282A	298	11.7	1044	41.1	850	125	S3550/ D3150	S7830/ D6940	9.00	DR08	14.8	18.6	D	B	75
13GBB676	A1ABB434	E 315/70R22.5 SL	18	S152/ D148	L	TL	GL282A	312	12.3	1014	39.9	850	125	S3550/ D3150	S7830/ D6940	9.00	DR08	14.8	18.6	D	B	75
13GBB693	11ABB412	E 315/80R22.5 SL	18	S154/ D150	M	TL	GL282A	312	12.3	1076	42.4	825	120	S3750/ D3350	S8270/ D7390	9.00	DR08	15.3	19.3	D	B	75
13GBB728	A1ABB480	E 315/80R22.5 SL	20	S156/ D150	L	TL	GL282A	312	12.3	1076	42.4	850	125	S4000/ D3750	S8820/ D7390	9.00	DR08	15.3	19.3	D	B	75

2013前进外贸轮胎-内页-ok.indd 14 2013-9-17 17:07:42

GL283A Regional Highway All-Position Radial

Product Features

- Completely new crown designing largely strengthens a tire's puncture resistance and effectively improve a tire's safety.
- Completely new tread cap recipe makes a tire have superstrong abrasion resistance.
- Modified chafer designing reflects excellent bead durability.
- Deepened pattern makes a tire have longer service life.
- Optimized groove designing guarantees a tire's wet skid resistance.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB714	A1ABB470	7.00R16	14	S118/ D114	L	TT	GL283A	200	7.9	782	30.8	770	110	S1320/ D1180	S2900/ D2600	5.50	DG04C	12.0	15.1			
13GBB561	11ABB331	7.50R16	14	S122/ D118	L	TT	GL283A	215	8.5	805	31.7	770	110	S1500/ D1320	S3305/ D2900	6.00	DG04C	14.0	17.6			
13GBB517	11ABB309	E 8.25R16	14	S126/ D122	L	TT	GL283A	235	9.3	855	33.7	670	97	S1700/ D1500	S3745/ D3305	6.50	DG05C	14.5	18.3			
13GBB732	A1ABB486	E 8.25R16	16	S128/ D124	K	TT	GL283A	235	9.3	855	33.7	770	110	S1800/ D1600	S3970/ D3525	6.50	DG05C	14.5	18.3			
13GBB795	11ABB460	7.00R20	14	S126/ D124	L	TT	GL283A	200	7.9	904	35.6	830	120	S1700/ D1600	S3750/ D3525	5.50	DG06C	13.0	16.4			
13GBB450	11ABB238	E 7.50R20 S	14	S130/ D128	K	TT	GL283A	215	8.5	935	36.8	830	120	S1900/ D1800	S4190/ D3970	6.00	DG06C	14.0	17.6			
13GBB604	11ABB276	E 8.25R20	14	S136/ D134	K	TT	GL283A	236	9.3	974	38.3	830	120	S2240/ D2120	S4940/ D4675	6.50	DG06C	14.5	18.3			
TBA	TBA	E 8.25R20	16	S139/ D137	J	TT	GL283A	236	9.3	974	38.3	930	135	S2430/ D2300	S5355/ D5070	6.50	DG06C	14.5	18.3			
13GBB475	11ABB286	E 9.00R20	16	S144/ D142	K	TT	GL283A	259	10.2	1019	40.1	900	130	S2800/ D2650	S6175/ D5840	7.00	DG07C	15.0	18.9			
13GBB477	A1ABB323	E 10.00R20 S	16	S146/ D143	K	TT	GL283A	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	15.5	19.5			
13GBB480	A1ABB326	E 10.00R20 S	18	S149/ D146	J	TT	GL283A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	15.5	19.5			
13GBB366	A1ABB258	E 11.00R20 S	16	S150/ D147	K	TT	GL283A	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	16.0	20.2			
13GBB536	11ABB314	E 11.00R20 S	18	S152/ D149	J	TT	GL283A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	16.0	20.2			
13GBB356	A1ABB247	12.00R20	16	S152/ D149	K	TT	GL283A	313	12.3	1122	44.2	760	110	S3550/ D3250	S7830/ D7160	8.50	DG09C	16.5	20.8			
13GBB357	A1ABB248	E 12.00R20 S	18	S154/ D151	K	TT	GL283A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	16.5	20.8			
13GBB272	A1ABB208	8R19.5	12	S124/ D122	L	TL	GL283A	203	8.0	859	33.8	760	110	S1600/ D1500	S3525/ D3305	6.00	CJ05	13.0	16.4			
13GBB740	A1ABB494	10R17.5	14	S134/ D132		TL	GL283A	252	10.0	854	33.6	800	115	S2120/ D2000	S4670/ D4410	7.50		13.0	16.4			
13GBB741	A1ABB495	10R17.5	16	S139/ D137	K	TL	GL283A	252	10.0	854	33.6	860	125	S2430/ D2300	S5355/ D5070	7.50		13.0	16.4			

2013前进外贸轮胎-内页-ok.indd 15 2013-9-17 17:07:44

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
TBA	TBA	E 9R22.5 S	12	S133/ D131	M	TL	GL283A	229	9.0	974	38.3	675	95	S2060/ D1950	S4540/ D4300	6.75	DR06	14.5	18.3			
13GBB298	A1ABB212	E 9R22.5 S	14	S136/ D134	M	TL	GL283A	229	9.0	974	38.3	830	120	S2240/ D2120	S4940/ D4675	6.75	DR06	14.5	18.3			
13GBB286	11ABB100	E 10R22.5 SL	14	S141/ D139	M	TL	GL283A	254	10.0	1020	40.2	790	115	S2575/ D2430	S5675/ D5355	7.50	DR06	15.0	18.9	D	C	76
13GBB513	11ABB301	E 10R22.5 SL	16	S144/ D142	L	TL	GL283A	254	10.0	1020	40.2	850	125	S2800/ D2650	S6175/ D5840	7.50	DR06	15.0	18.9	D	C	76
13GBB215	A1ABB151	11R22.5	14	S144/ D142	M	TL	GL283A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	14.8	18.6			
13GBB222	A1ABB158	E 11R22.5 SL	16	S146/ D143	M	TL	GL283A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	14.8	18.6	C	C	76
13GBB577	11ABB347	E 12R22.5 S	16	S150/ D147	M	TL	GL283A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	16.0	20.2			
TBA	TBA	E 12R22.5 S	18	S152/ D148	L	TL	GL283A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	16.0	20.2			
13GBB377	A1ABB163	E 11R24.5 S	14	S146/ D143	M	TL	GL283A	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	15.0	18.9			
13GBB231	A1ABB167	E 11R24.5 S	16	S149/ D146	L	TL	GL283A	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	15.0	18.9			
13GBB526	A1ABB351	E 13R22.5	18	S154/ D150	K	TL	GL283A	320	12.6	1124	44.3	850	125	S3750/ D3350	S8270/ D7390	9.75	DR08	16.5	20.8			
TBA	TBA	E 13R22.5	20	S156/ D150	J	TL	GL283A	320	12.6	1124	44.3	875	130	S4000/ D3350	S8820/ D7390	9.75	DR08	16.5	20.8			
13GBB378	A1ABB178	E 215/75R17.5 SL	12	S126/ D124	M	TL	GL283A	212	8.3	767	30.2	700	100	S1700/ D1600	S3750/ D3525	6.00	DR04	12.0	15.1	D	C	76
13GBB280	11ABB241	E 215/75R17.5 SL	16	S135/ D133	J	TL	GL283A	212	8.3	767	30.2	860	125	S2180/ D2060	S4805/ D4540	6.00	DR04	12.0	15.1	D	C	76
13GBB246	A1ABB182	E 235/75R17.5 SL	14	S132/ D130	M	TL	GL283A	233	9.2	797	31.4	775	110	S2000/ D1900	S4410/ D4190	6.75	DR05	13.0	16.4	D	C	76
13GBB379	A1ABB183	E 235/75R17.5 SL	16	S143/ D141	J	TL	GL283A	233	9.2	797	31.4	860	125	S2725/ D2575	S6005/ D5675	6.75	DR05	13.0	16.4	D	C	76
TBA	TBA	E 225/70R19.5 S	12	S125/ D123	M	TL	GL283A	226	8.9	811	31.9	660	95	S1650/ D1550	S3640/ D3415	6.75	DR06	13.0	16.4			
13GBB244	A1ABB180	E 225/70R19.5 S	14	S128/ D126	L	TL	GL283A	226	8.9	811	31.9	700	100	S1800/ D1700	S3970/ D3750	6.75	DR06	13.0	16.4			
13GBB248	A1ABB184	E 245/70R19.5 SL	16	S136/ D134	M	TL	GL283A	248	9.8	839	33.0	825	120	S2240/ D2120	S4940/ D4675	7.50	DR06	14.0	17.6	D	C	76
13GBB249	A1ABB185	265/70R19.5	14	S137/ D134	M	TL	GL283A	262	10.3	867	34.1	760	110	S2300/ D2120	S5070/ D4675	7.50	DR06	13.0	16.4			
13GBB250	A1ABB186	E 265/70R19.5 SL	16	S140/ D138	M	TL	GL283A	262	10.3	867	34.1	775	110	S2500/ D2360	S5510/ D5205	7.50	DR06	13.0	16.4	D	C	76
13GBB558	11ABB328	E 265/70R19.5 SL	18	S143/ D141	J	TL	GL283A	262	10.3	867	34.1	850	125	S2725/ D2575	S6005/ D5675	7.50	DR06	13.0	16.4	D	C	76
13GBB203	A1ABB139	E 255/70R22.5 SL	16	S140/ D137	M	TL	GL283A	255	10.0	930	36.6	800	115	S2500/ D2300	S5510/ D5070	7.50	DR06	14.0	17.6	D	C	76
13GBB251	A1ABB187	E 275/70R22.5 SL	16	S144/ D141	M	TL	GL283A	276	10.9	958	37.7	830	120	S2800/ D2575	S6175/ D5675	8.25	DR07	13.0	16.4	D	C	76
13GBB552	11ABB322	E 275/70R22.5 SL	18	S148/ D145	K	TL	GL283A	276	10.9	958	37.7	900	130	S3150/ D2900	S6940/ D6395	8.25	DR07	13.0	16.4	D	C	76
13GBB567	11ABB337	275/80R22.5	16	S146/ D143	M	TL	GL283A	275	10.8	1036	40.8	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	15.0	18.9			
13GBB254	A1ABB190	E 285/75R24.5 S	14	S144/ D141	M	TL	GL283A	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	15.0	18.9			
13GBB258	A1ABB194	E 285/75R24.5 S	16	S147/ D144	L	TL	GL283A	283	11.1	1052	41.4	830	120	S3075/ D2800	S6780/ D6175	8.25	DR07	15.0	18.9			
13GBB373	A1ABB268	E 295/75R22.5 S	14	S144/ D141	M	TL	GL283A	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	15.0	18.9			
13GBB266	A1ABB202	E 295/75R22.5 S	16	S146/ D143	L	TL	GL283A	298	11.7	1014	39.9	830	120	S3000/ D2725	S6610/ D6005	9.00	DR08	15.0	18.9			

2013前进外贸轮胎-内页-ok.indd 16 2013-9-17 17:07:45

GL283A L.E.T. Regional Highway All-Position Radial

Product Features

- Completely new crown designing largely strengthens a tire's puncture resistance and effectively improve a tire's safety.
- Completely new tread cap recipe makes a tire have superstrong abrasion resistance.
- Modified chafer designing reflects excellent bead durability.
- Deepened pattern makes a tire have longer service life.
- Optimized groove designing guarantees a tire's wet skid resistance.

Recommended Vehicle Types & Position

SmartWay®

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB681	A1ABB437	11R22.5	14	S144/ D142	M	TL	GL283A LET	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	14.8	18.6			
13GBB682	A1ABB438	E 11R22.5 S L	16	S146/ D143	M	TL	GL283A LET	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	14.8	18.6	C	C	76
13GBB683	A1ABB439	E 11R24.5 S	14	S146/ D143	M	TL	GL283A LET	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	15.0	18.9			
13GBB684	A1ABB440	E 11R24.5 S	16	S149/ D146	L	TL	GL283A LET	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	15.0	18.9			
13GBB685	A1ABB441	E 285/75R24.5 S	14	S144/ D141	M	TL	GL283A LET	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	15.0	18.9			
13GBB686	A1ABB442	E 285/75R24.5 S	16	S147/ D144	L	TL	GL283A LET	283	11.1	1050	41.3	830	120	S3075/ D2800	S6780/ D6175	8.25	DR07	15.0	18.9			
13GBB687	A1ABB443	E 295/75R22.5 S	14	S144/ D141	M	TL	GL283A LET	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	15.0	18.9			
13GBB688	A1ABB444	E 295/75R22.5 S	16	S146/ D143	L	TL	GL283A LET	298	11.7	1014	39.9	830	120	S3000/ D2725	S6610/ D6005	9.00	DR08	15.0	18.9			

2013前进外贸轮胎-内页-ok.indd 17 2013-9-17 17:07:47

GL286A Regional Highway All-Position Radial

Product Features

- Excellent recipe makes a tire have superstrong abrasion resistance.
- Optimized crown designing makes a tire have good puncture resistance and better durability.
- Strengthened carcass designing makes a tire have overlong service life and can be retreaded several times.
- Strengthened chafer designing makes a tire have excellent carrying property.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB793	A1ABB523	425/65R22.5	20	165	K	TL	GL286A	430	16.9	1124	44.3	825	120	5150	11400	12.25		16.5	20.8			

2013前进外贸轮胎-内页-ok.indd 18 2013-9-17 17:07:47

GL288A Regional Highway All-Position Radial

Product Features

- Use double tread structure makes a tire generate less heat.
- Optimized belt structure designing, which strengthens the rigidity and flex at crown area, guarantees a tire's unifrom wear.
- Optimized tread recipe designing improves the a tire's applicability to the road surface.
- Deepen pattern height makes a tire service longer.
- Wider tread cap width makes a tire's contact patch bigger and wear better.
- Optimized tread profile designing makes a tire's contact pressure more uniform.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB057	11ABB047	E 10.00R20 S	16	S146/ D143	K	TT	GL288A	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	14.0	17.6			
13GBB535	11ABB315	E 10.00R20 S	18	S149/ D146	J	TT	GL288A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	14.0	17.6			
13GBB453	11ABB278	E 11.00R20 S	16	S150/ D147	K	TT	GL288A	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	14.5	18.3			
13GBB342	11ABB134	E 11.00R20 S	18	S152/ D149	J	TT	GL288A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	14.5	18.3			
13GBB170	11ABB078	12.00R20	16	S152/ D149	K	TT	GL288A	313	12.3	1122	44.2	760	110	S3550/ D3250	S7830/ D7160	8.50	DG09C	15.0	18.9			
13GBB385	11ABB233	E 12.00R20 S	18	S154/ D151	K	TT	GL288A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	15.0	18.9			
TBA	TBA	E 12.00R20 S	20	S156/ D153	J	TT	GL288A	313	12.3	1122	44.2	900	130	S4000/ D3650	S8820/ D8050	8.50	DG09C	15.0	18.9			
13GBB217	A1ABB153	11R22.5	14	S144/ D142	M	TL	GL288A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	13.5	17.0			
13GBB224	A1ABB160	E 11R22.5 S	16	S148/ D144	M	TL	GL288A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	13.5	17.0			
13GBB305	11ABB116	E 12R22.5 S	16	S150/ D147	M	TL	GL288A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	14.5	18.3			
TBA	TBA	E 12R22.5 S	18	S152/ D148	L	TL	GL288A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	14.5	18.3			
13GBB397	A1ABB313	E 13R22.5	18	S154/ D150	K	TL	GL288A	320	12.6	1124	44.3	850	125	S3750/ D3350	S8270/ D7390	9.75	DR08	15.0	18.9			
13GBB626	A1ABB383	E 13R22.5	20	S156/ D150	J	TL	GL288A	320	12.6	1124	44.3	875	130	S4000/ D3350	S8820/ D7390	9.75	DR08	15.0	18.9			

2013前进外贸轮胎-内页-ok.indd 19 2013-9-17 17:07:49

GL291A Regional Highway All-Position Radial

Product Features

- Unique corner design of the groove can avoid irregular wear of the pattern.
- Unique groove bottom makes a tire have good self-clean property, which can effectively protect crown.
- Larger lateral groove at shoulder area guarantees a tire have better traction and grip.
- Optimized belt structure designing strengthens the rigidity and flex at crown, which can guarantes the uniform wear of the tire.
- Specialized designed recipe guarantees a tire's tear resistance and cost performance ratio at complex condition.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB281	11ABB110	12.00R24	18	S158/ D155	K	TT	GL291A	323	12.4	1216	47.9	830	120	S4250/ D3875	S9370/ D8540	8.50	DG09C	16.0	20.2			
13GBB407	11ABB247	12.00R24	20	S160/ D157	K	TT	GL291A	323	12.4	1216	47.9	900	130	S4500/ D4125	S9920/ D9090	8.50	DG09C	16.0	20.2			

2013前进外贸轮胎-内页-ok.indd 20 2013-9-17 17:07:50

GL296A Regional Highway All-Position Radial

Product Features

- Use double tread structure makes a tire generate less heat.
- Lower rolling resistance and fuel consumption.
- Wider tread and deeper pattern make a tire have excellent abrasion resistance.
- Optimized tread profile design makes contact pressure distribution more uniform.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB207	A1ABB144	E 295/80R22.5 S	16	S150/ D146	M	TL	GL296A	298	11.7	1044	41.1	800	115	S3350/ D3075	S7390/ D6780	9.00	DR08	15.5	19.5			
13GBB550	11ABB320	E 295/80R22.5 S	18	S152/ D148	L	TL	GL296A	298	11.7	1044	41.1	850	125	S3550/ D3250	S7830/ D7160	9.00	DR08	15.5	19.5			
13GBB269	A1ABB205	E 315/80R22.5 S	18	S154/ D150	M	TL	GL296A	312	12.3	1076	42.4	825	120	S3750/ D3350	S8270/ D7390	9.00	DR08	16.5	20.8			
13GBB277	11ABB245	E 315/80R22.5 S	20	S156/ D150	L	TL	GL296A	312	12.3	1076	42.4	850	125	S4000/ D3750	S8820/ D7390	9.00	DR08	16.5	20.8			

2013前进外贸轮胎-内页-ok.indd 21 2013-9-17 17:07:51

GL216D Regional Highway Drive-Position Radial

Product Features

- Wider crown design,better operational stability of tire.
- Use dual tread structure, lower heat build up of tire.
- Completely new protection design of groove bottom, largely strengthens resistance to puncture,and effectively improves resistance to crown blowout.
- Optimized geometrical shape of the pattern can guarantee a tire with excellent wet skid resistance.
- Wider tread and deeper pattern, more excellent abrasion resistance and longer mileage.
- Unidirectional pattern design and unique block designing provide excellent driving performance.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB787	A1ABB517	11R22.5	16	S146/ D143	M	TL	GL216D	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	19.5	24.6			
13GBB788	A1ABB518	11R22.5	18	S148/ D145	L	TL	GL216D	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	19.5	24.6			
13GBB723	11ABB418	12R22.5	16	S150/ D147	M	TL	GL216D	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	20.0	25.2			
13GBB776	11ABB449	12R22.5	18	S152/ D148	L	TL	GL216D	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	20.0	25.2			

2013前进外贸轮胎-内页-ok.indd 22 2013-9-17 17:07:52

GL226D Regional Highway Drive-Position Radial

Product Features

- Wider crown makes a tire has better operational stability.
- Use the double tread structure makes a tire generate less heat.
- Completely new designing of groove bottom protection largely strengthens puncture resistance and effectively improves the properties of crown blowout.
- Optimized geometrical shape of the pattern can guarantee a tire with excellent wet skid resistance.
- Wider tread and deeper pattern have more excellent abrasion resistance and longer service life.
- Unidirectional pattern designing and unique block designing provide excellent driving properties.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB798	TBA	11R22.5	16	S146/ D143	M	TL	GL226D	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	19.5	24.6			
13GBB799	TBA	11R22.5	18	S148/ D145	L	TL	GL226D	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	19.5	24.6			
13GBB738	A1ABB493	12R22.5	16	S150/ D147	M	TL	GL226D	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	20.0	25.2			
13GBB778	11ABB451	12R22.5	18	S152/ D148	L	TL	GL226D	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	20.0	25.2			

2013前进外贸轮胎-内页-ok.indd 23 2013-9-17 17:07:53

GL266D Regional Highway Drive-Position Radial

Product Features

- Extra deep pattern makes a tire have overlong service life and lower cost.
- Firm shoulder area designing makes shouder deformation less which effectively prevents irregular wear.
- Thick and strong pattern designing can provide strong driving force and braking force.
- Use self-clean technology at groove makes tread have excellent self-clean property.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB699	A1ABB453	11R22.5	14	S144/ D142	M	TL	GL266D	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	19.7	24.8			
13GBB700	A1ABB455	E 11R22.5	16	S146/ D143	M	TL	GL266D	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	19.7	24.8			
13GBB703	A1ABB459	E 11R24.5	14	S146/ D143	M	TL	GL266D	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	19.7	24.8			
13GBB704	A1ABB460	E 11R24.5	16	S149/ D146	L	TL	GL266D	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	19.7	24.8			
13GBB707	A1ABB463	E 285/75R24.5	14	S144/ D141	M	TL	GL266D	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	19.7	24.8			
13GBB708	A1ABB464	E 285/75R24.5	16	S147/ D144	L	TL	GL266D	283	11.1	1050	41.3	830	120	S3075/ D2800	S6780/ D6175	8.25	DR07	19.7	24.8			
13GBB709	A1ABB465	E 295/75R22.5	14	S144/ D141	M	TL	GL266D	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	19.7	24.8			
13GBB710	A1ABB466	E 295/75R22.5	16	S146/ D143	L	TL	GL266D	298	11.7	1014	39.9	830	120	S3000/ D2725	S6610/ D6005	9.00	DR08	19.7	24.8			

2013前进外贸轮胎-内页-ok.indd 24 2013-9-17 17:07:55

GL266D ULT Regional Highway Drive-Position Radial

Product Features

- Extra deep pattern makes a tire have overlong service life and lower cost.
- Firm shoulder area designing makes shouder deformation less which effectively prevents irregular wear.
- Thick and strong pattern designing can provide strong driving force and braking force.
- Use self-clean technology at groove makes tread have excellent self-clean property.
- Extra deep pattern can get longer service life.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB211	A1ABB147	11R22.5	14	S144/ D142	M	TL	GL266D ULT	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	25.5	32.1			
13GBB218	A1ABB154	11R22.5	16	S146/ D143	M	TL	GL266D ULT	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	25.5	32.1			
13GBB225	A1ABB161	[E] 11R24.5	14	S146/ D143	M	TL	GL266D ULT	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	25.5	32.1			
13GBB229	A1ABB165	[E] 11R24.5	16	S149/ D146	L	TL	GL266D ULT	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	25.5	32.1			
13GBB252	A1ABB188	[E] 285/75R24.5	14	S144/ D141	M	TL	GL266D ULT	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	25.5	32.1			
13GBB256	A1ABB192	[E] 285/75R24.5	16	S147/ D144	L	TL	GL266D ULT	283	11.1	1050	41.3	830	120	S3075/ D2800	S6780/ D6175	8.25	DR07	25.5	32.1			
13GBB372	A1ABB267	[E] 295/75R22.5	14	S144/ D141	M	TL	GL266D ULT	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	25.5	32.1			
13GBB264	A1ABB200	[E] 295/75R22.5	16	S146/ D143	L	TL	GL266D ULT	298	11.7	1014	39.9	830	120	S3000/ D2725	S6610/ D6005	9.00	DR08	25.5	32.1			

2013前进外贸轮胎-内页-ok.indd 25 2013-9-17 17:07:56

GL267D Regional Highway Drive-Position Radial

Product Features

- Completely optimized structure and recipe designing makes a tire have better cost performance ratio.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.
- Use the double tread structure makes a tire generate less heat.
- Optimized pattern shape designing gurantees a tire has excellent wet skid resistance.
- Unidirectional pattern designing and unique block designing provide excellent driving properties.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
TBA	11ABB410	E 12R22.5 SL	16	S150/ D147	M	TL	GL267D	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	17.8	22.4	D	C	75
TBA	TBA	E 12R22.5 SL	18	S152/ D148	L	TL	GL267D	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	17.8	22.4	D	C	75
13GBB673	A1ABB430	E 295/80R22.5 SL	16	S150/ D146	M	TL	GL267D	298	11.7	1044	41.1	800	115	S3350/ D3000	S7390/ D6610	9.00	DR08	17.8	22.4	D	C	75
13GBB729	A1ABB482	E 295/80R22.5 SL	18	S152/ D148	L	TL	GL267D	298	11.7	1044	41.1	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	17.8	22.4	D	C	75
13GBB675	A1ABB432	E 315/70R22.5 SL	18	S152/ D148	L	TL	GL267D	312	12.3	1014	39.9	850	125	S3550/ D3150	S7830/ D6940	9.00	DR08	17.8	22.4	D	C	75
13GBB628	11ABB383	E 315/80R22.5 SL	18	S154/ D150	M	TL	GL267D	312	12.3	1076	42.4	825	120	S3750/ D3350	S8270/ D7390	9.00	DR08	17.8	22.4	E	C	75
13GBB730	A1ABB483	E 315/80R22.5 SL	20	S156/ D150	L	TL	GL267D	312	12.3	1076	42.4	850	125	S4000/ D3750	S8820/ D7390	9.00	DR08	17.8	22.4	E	C	75

2013前进外贸轮胎-内页-ok.indd 26 2013-9-17 17:07:57

GL268D Regional Highway Drive-Position Radial

Product Features

- Use the double tread structure makes a tire generate less heat.
- Optimized pattern shape designing gurantees a tire has excellent wet skid resistance.
- Wider tread and deeper pattern makes a tire have more excellent abrasion resistance and longer service life.
- Unidirectional pattern designing and unique block designing provide excellent driving properties.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
TBA	TBA	E 10.00R20 S	16	S146/ D143	K	TT	GL268D	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	20.0	25.2			
13GBB352	11ABB144	E 10.00R20 S	18	S149/ D146	K	TT	GL268D	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	20.0	25.2			
13GBB174	11ABB084	E 11.00R20 S	16	S150/ D147	K	TT	GL268D	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	20.5	25.8			
13GBB175	11ABB085	12.00R20	16	S152/ D149	K	TT	GL268D	313	12.3	1122	44.2	760	110	S3550/ D3250	S7830/ D7160	8.50	DG09C	20.5	25.8			
13GBB177	11ABB237	E 12.00R20 S	18	S154/ D151	K	TT	GL268D	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	20.5	25.8			
13GBB212	A1ABB148	11R22.5	14	S144/ D142	M	TL	GL268D	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	20.5	25.8			
A1ABB264	A1ABB264	E 11R22.5 SL	16	S146/ D143	M	TL	GL268D	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	20.5	25.8	D	B	76
13GBB789	A1ABB521	E 11R22.5 SL	18	S148/ D145	L	TL	GL268D	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	20.5	25.8	D	B	76
13GBB376	A1ABB162	E 11R24.5 S	14	S146/ D143	M	TL	GL268D	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	20.5	25.8			
13GBB230	A1ABB166	E 11R24.5 S	16	S149/ D146	L	TL	GL268D	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	20.5	25.8			
13GBB364	A1ABB255	E 12R22.5 S	16	S150/ D147	M	TL	GL268D	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	20.5	25.8			
TBA	TBA	E 12R22.5 S	18	S152/ D148	L	TL	GL268D	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	20.5	25.8			
13GBB528	A1ABB353	E 13R22.5	18	S154/ D150	K	TL	GL268D	320	12.6	1124	44.3	850	125	S3750/ D3350	S8270/ D7390	9.75	DR08	21.0	26.5			
13GBB733	A1ABB488	E 13R22.5	20	S156/ D150	J	TL	GL268D	320	12.6	1124	44.3	875	130	S4000/ D3350	S8820/ D7390	9.75	DR08	21.0	26.5			
TBA	TBA	E 225/70R19.5	12	S125/ D123	M	TL	GL268D	226	8.9	811	31.9	660	95	S1650/ D1550	S3640/ D3415	6.75	DR06	17.0	21.4			
13GBB522	A1ABB347	E 225/70R19.5	14	S128/ D126	L	TL	GL268D	226	8.9	811	31.9	700	100	S1800/ D1700	S3970/ D3750	6.75	DR06	17.0	21.4			
13GBB500	A1ABB336	245/70R19.5	16	136/134	J	TL	GL268D	248	9.8	839	33.0	830	120	S2240/ D2120	S4940/ D4675	7.50	DR06	17.0	21.4			
13GBB253	A1ABB189	E 285/75R24.5 S	14	S144/ D141	M	TL	GL268D	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	20.5	25.8			
13GBB257	A1ABB193	E 285/75R24.5 S	16	S147/ D144	L	TL	GL268D	283	11.1	1050	41.3	830	120	S3075/ D2800	S6780/ D6175	8.25	DR07	20.5	25.8			
13GBB261	A1ABB197	E 295/75R22.5 S	14	S144/ D141	M	TL	GL268D	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	20.5	25.8			
13GBB265	A1ABB201	E 295/75R22.5 S	16	S146/ D143	L	TL	GL268D	298	11.7	1014	39.9	830	120	S3000/ D2725	S6610/ D6005	9.00	DR08	20.5	25.8			
13GBB206	A1ABB143	E 295/80R22.5 S	16	S150/ D146	M	TL	GL268D	298	11.7	1044	41.1	800	115	S3350/ D3075	S7390/ D6780	9.00	DR08	23.0	29.0			
13GBB549	11ABB319	E 295/80R22.5 S	18	S152/ D148	L	TL	GL268D	298	11.7	1044	41.1	850	125	S3550/ D3250	S7830/ D7160	9.00	DR08	23.0	29.0			
13GBB268	A1ABB204	E 315/80R22.5 S	18	S154/ D150	M	TL	GL268D	312	12.3	1076	42.4	825	120	S3750/ D3350	S8270/ D7390	9.00	DR08	23.0	29.0			
13GBB279	11ABB108	E 315/80R22.5 S	20	S156/ D150	L	TL	GL268D	312	12.3	1076	42.4	850	125	S4000/ D3750	S8820/ D7390	9.00	DR08	23.0	29.0			

2013前进外贸轮胎-内页-ok.indd 27 2013-9-17 17:07:58

GL275D Regional Highway Drive-Position Radial

Product Features

- Optimized belt structure strengthens the rigidity and flex at crown area which can guarantee the uniform wear of a tire.
- Firm and strong block provides strong traction.
- Firm and strong block and reinforcing ribs interconnecting at shoulder area guarantee good traction.
- Reasonable central connected ""Z"" circumferential block makes a uniform stress distribution at central and shoulder areas,therefore acquire longer service life.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB213	A1ABB149	11R22.5	14	S144/ D142	M	TL	GL275D	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	17.0	21.4			
13GBB220	A1ABB156	[E] 11R22.5	16	S146/ D143	M	TL	GL275D	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	17.0	21.4			

2013前进外贸轮胎-内页-ok.indd 28 2013-9-17 17:07:59

GL293D Regional Highway Drive-Position Radial

Product Features

- Optimized belt structure design strengthens the rigidity and flex at crown which guarantees the uniform wear of the tire.
- Double tread recipe design guarantees a tire have optimum abrasion resistance.
- Optimized tread profile shape guarantees bigger contact patch and uniform wear.
- Unique pattern design provides strong traction and braking force.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB158	11ABB079	E 11.00R20 S	16	S150/ D147	K	TT	GL293D	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	20.5	25.8			
13GBB532	11ABB311	E 11.00R20 S	18	S152/ D149	J	TT	GL293D	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	20.5	25.8			
13GBB171	11ABB080	12.00R20	16	S152/ D149	K	TT	GL293D	313	12.3	1122	44.2	760	110	S3550/ D3250	S7830/ D7160	8.50	DG09C	20.5	25.8			
13GBB061	11ABB051	E 12.00R20 S	18	S154/ D151	K	TT	GL293D	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	20.5	25.8			
TBA	TBA	E 12.00R20 S	20	S156/ D153	J	TT	GL293D	313	12.3	1122	44.2	900	130	S4000/ D3650	S8820/ D8050	8.50	DG09C	20.5	25.8			
13GBB701	A1ABB457	11R22.5	14	S144/ D142	M	TL	GL293D	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	17.8	22.4			
13GBB702	A1ABB458	E 11R22.5 S	16	S146/ D143	M	TL	GL293D	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	17.8	22.4			
13GBB705	A1ABB461	E 11R24.5 S	14	S146/ D143	M	TL	GL293D	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	17.8	22.4			
13GBB706	A1ABB462	E 11R24.5 S	16	S149/ D146	L	TL	GL293D	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	17.8	22.4			
13GBB292	A1ABB213	E 12R22.5 S	16	S150/ D147	M	TL	GL293D	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	20.5	25.8			
TBA	TBA	E 12R22.5 S	18	S152/ D148	L	TL	GL293D	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	20.5	25.8			
13GBB724	A1ABB476	E 285/75R24.5	14	S144/ D141	M	TL	GL293D	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	17.8	22.4			
13GBB725	A1ABB477	E 285/75R24.5	16	S147/ D144	L	TL	GL293D	283	11.1	1050	41.3	830	120	S3075/ D2800	S6780/ D6175	8.25	DR07	17.8	22.4			
13GBB711	A1ABB467	E 295/75R22.5	14	S144/ D141	M	TL	GL293D	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	17.8	22.4			
13GBB712	A1ABB468	E 295/75R22.5	16	S146/ D143	L	TL	GL293D	298	11.7	1014	39.9	830	120	S3000/ D2725	S6610/ D6005	9.00	DR08	17.8	22.4			

2013前进外贸轮胎-内页-ok.indd 29 2013-9-17 17:08:01

GL293D L.E.T. Regional Highway Drive-Position Radial

Product Features

- Optimized belt structure design strengthens the rigidity and flex at crown which guarantees the uniform wear of the tire.
- Double tread recipe design guarantees a tire have optimum abrasion resistance.
- Optimized tread profile shape guarantees bigger contact patch and uniform wear.
- Unique pattern design provides strong traction and braking force.

Recommended Vehicle Types & Position

SmartWay®

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB717	TBA	[E] 11R22.5 [S]	16	S146/ D143	M	TL	GL293D LET	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	17.8	22.4			
13GBB718	TBA	[E] 11R24.5 [S]	16	S149/ D146	L	TL	GL293D LET	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	17.8	22.4			
13GBB719	TBA	[E] 285/75R24.5	14	S144/ D141	M	TL	GL293D LET	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	17.8	22.4			
13GBB720	TBA	[E] 295/75R22.5	14	S144/ D141	M	TL	GL293D LET	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	17.8	22.4			

2013前进外贸轮胎-内页-ok.indd 30 2013-9-17 17:08:01

GL293D ULT Regional Highway Drive-Position Radial

Product Features

- Optimized belt structure design strengthens the rigidity and flex at crown which guarantees the uniform wear of the tire.
- Double tread recipe design guarantees a tire have optimum abrasion resistance.
- Optimized tread profile shape guarantees bigger contact patch and uniform wear.
- Unique pattern design provides strong traction and braking force.
- Extra deep pattern can get longer service life.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB458	A1ABB317	11R22.5	14	S144/ D142	M	TL	GL293D ULT	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	19.5	24.6			
13GBB460	A1ABB318	11R22.5	16	S146/ D143	M	TL	GL293D ULT	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	19.5	24.6			
13GBB468	11ABB148	E 11R24.5 S	14	S146/ D143	M	TL	GL293D ULT	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	19.2	24.2			
13GBB470	11ABB150	E 11R24.5 S	16	S149/ D146	L	TL	GL293D ULT	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	19.2	24.2			
13GBB506	A1ABB342	E 285/75R24.5	14	S144/ D141	M	TL	GL293D ULT	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	19.5	24.6			
13GBB508	A1ABB344	E 285/75R24.5	16	S147/ D144	L	TL	GL293D ULT	283	11.1	1050	41.3	830	120	S3075/ D2800	S6780/ D6175	8.25	DR07	19.5	24.6			
13GBB502	A1ABB338	E 295/75R22.5	14	S144/ D141	M	TL	GL293D ULT	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	19.5	24.6			
13GBB504	A1ABB340	E 295/75R22.5	16	S146/ D143	L	TL	GL293D ULT	298	11.7	1014	39.9	830	120	S3000/ D2725	S6610/ D6005	9.00	DR08	19.5	24.6			

2013前进外贸轮胎-内页-ok.indd 31 2013-9-17 17:08:02

GL250T Regional Highway Trailer-Position Radial

Product Features

- Excellent recipe makes a tire has superstrong abrasion resistance.
- Optimized crown designing makes a tire has good puncture resistance and better durability.
- Strengthened carcass designing makes a tire has longer service life and can be retreaded several times.
- Strengthened chafer designing makes a tire has excellent carrying property.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB634	A1ABB385	[E] 385/65R22.5 [S]	18	158	L	TL	GL250T	389	15.3	1072	42.2	850	125	S4250	S9370	11.75		16.2	20.4			
13GBB637	A1ABB388	[E] 385/65R22.5 [S]	20	160	K	TL	GL250T	389	15.3	1072	42.2	900	130	S4500	S9920	11.75		16.2	20.4			

2013前进外贸轮胎-内页-ok.indd 32 2013-9-17 17:08:03

GL260T Regional Highway Trailer-Position Radial

Product Features

- Excellent recipe makes a tire have superstrong abrasion resistance.
- Optimized crown designing makes a tire have good puncture resistance and better durability.
- Strengthened carcass designing makes a tire have overlong service life and can be retreaded several times.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
TBA	11ABB414	8.25R15	14	129/127	M	TT	GL260T	234	9.2	836	32.9	830	120	S1850/ D1750	S4080/ D3860	6.50		11.0	13.9			
TBA	TBA	8.25R15	18	143/141	G	TT	GL260T	234	9.2	836	32.9	850	125	S2725/ D2575	S6005/ D5675	6.50		11.0	13.9			

2013前进外贸轮胎-内页-ok.indd 33 2013-9-17 17:08:15

GL283T Regional Highway Trailer-Position Radial

Product Features

- Completely new crown designing largely strengthens a tire's puncture resistance and effectively improve a tire's safety.
- Completely new tread cap recipe makes a tire have superstrong abrasion resistance.
- Modified chafer designing reflects excellent bead durability.
- Deepened pattern makes a tire have longer service life.
- Optimized groove designing guarantees a tire's wet skid resistance.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB553	11ABB323	E 215/75R17.5 S.L	12	S126/ D124	M	TL	GL283T	212	8.3	767	30.2	700	100	S1700/ D1600	S3750/ D3525	6.00	DR04	12.0	15.1	D	C	76
13GBB555	11ABB325	E 215/75R17.5 S.L	16	S135/ D133	J	TL	GL283T	212	8.3	767	30.2	860	125	S2180/ D2060	S4805/ D4540	6.00	DR04	12.0	15.1	D	C	76
13GBB556	11ABB326	E 235/75R17.5 S.L	14	S132/ D130	M	TL	GL283T	233	9.2	797	31.4	775	110	S2000/ D1900	S4410/ D4190	6.75	DR05	13.0	16.4	D	C	76
13GBB557	11ABB327	E 235/75R17.5 S.L	16	S143/ D141	J	TL	GL283T	233	9.2	797	31.4	860	125	S2725/ D2575	S6005/ D5675	6.75	DR05	13.0	16.4	D	C	76

2013前进外贸轮胎-内页-ok.indd 34 2013-9-17 17:08:16

GL285T Regional Highway Trailer-Position Radial

Product Features

- Excellent recipe makes a tire have superstrong abrasion resistance and high speed performance.
- Four straight line formed circumferential groove at center makes a tire have excellent overall property at trailer position.
- Unique small and narrow sipes and lateral patterns make a tire have good traction under wet road surfaces.
- Use unique decoupling designing at shoulder can effectively prevent a tire's irregular wear.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB618	11ABB379	ST235/85R16	12	128	L	TL	GL285T	236	9.3	805	31.7	655	95	1800	3960	6.50		8.0	10.0			
13GBB216	A1ABB152	11R22.5	14	S144/ D142	M	TL	GL285T	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	9.5	12.0			
13GBB223	A1ABB159	E 11R22.5	16	S146/ D143	M	TL	GL285T	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	9.5	12.0			
13GBB371	A1ABB265	E 11R24.5	14	S146/ D143	M	TL	GL285T	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	9.5	12.0			
13GBB232	A1ABB168	E 11R24.5	16	S149/ D146	L	TL	GL285T	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	9.5	12.0			
13GBB255	A1ABB191	E 285/75R24.5	14	S144/ D141	M	TL	GL285T	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	9.5	12.0			
13GBB259	A1ABB195	E 285/75R24.5	16	S147/ D144	L	TL	GL285T	283	11.1	1050	41.3	830	120	S3075/ D2800	S6780/ D6175	8.25	DR07	9.5	12.0			
13GBB374	A1ABB270	E 295/75R22.5	14	S144/ D141	M	TL	GL285T	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	9.5	12.0			
13GBB267	A1ABB203	E 295/75R22.5	16	S146/ D143	L	TL	GL285T	298	11.7	1014	39.9	830	120	S3000/ D2725	S6610/ D6005	9.00	DR08	9.5	12.0			

2013前进外贸轮胎-内页-ok.indd 35 2013-9-17 17:08:17

GL286T Regional Highway Trailer-Position Radial

Product Features

- Excellent recipe makes a tire have superstrong abrasion resistance.
- Optimized crown designing makes a tire have good puncture resistance and better durability.
- Strengthened carcass designing makes a tire have overlong service life and can be retreaded several times.
- Strengthened chafer designing makes a tire have excellent carrying property.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB271	A1ABB207	^{E}385/65R22.5 ^{S,L}	18	158	L	TL	GL286T	389	15.3	1072	42.2	850	125	S4250	S9370	11.75		15.5	19.5	D	B	76
13GBB546	A1ABB365	^{E}385/65R22.5 ^{S,L}	20	160	K	TL	GL286T	389	15.3	1072	42.2	900	130	S4500	S9920	11.75		15.5	19.5	D	B	76
13GBB202	A1ABB137	425/65R22.5	20	165	K	TL	GL286T	430	16.9	1124	44.3	825	120	5150	11400	12.25		16.5	20.8			

2013前进外贸轮胎-内页-ok.indd 36 2013-9-17 17:08:18

GL298T Regional Highway Trailer-Position Radial

Product Features

- Use double tread structure makes a tire generate less heat and have superstrong durability.
- Optimized belt structure designing, which strengthens the rigidity and flex at crown area, guarantees a tire's unifrom wear.
- Wider tread and deeper pattern have more excellent abrasion resistance.
- Use bead structure with design patent makes a tire have excellent carrying ability.
- Optimized tread profile design makes contact pressure distribution more uniform.
- Optimized tread recipe improves the applicability to bad road conditons.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB172	11ABB081	12.00R20	16	S152/ D149	K	TT	GL298T	313	12.3	1122	44.2	760	110	S3550/ D3250	S7830/ D7160	8.50	DG09C	16.5	20.8			
13GBB098	A1ABB071	[E] 12.00R20	18	S154/ D151	K	TT	GL298T	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	16.5	20.8			
TBA	TBA	[E] 12.00R20	20	S156/ D153	J	TT	GL298T	313	12.3	1122	44.2	900	131	S4000/ D3650	S8820/ D8050	8.50	DG09C	16.5	20.8			

2013前进外贸轮胎-内页-ok.indd 37 2013-9-17 17:08:18

GL299T Regional Highway Trailer-Position Radial

Product Features

- Use double tread structure makes a tire generate less heat and have superstrong durability.
- Optimized belt structure designing, which strengthens the rigidity and flex at crown area, guarantees a tire's unifrom wear.
- Wider tread and deeper pattern have more excellent abrasion resistance.
- Use bead structure with design patent makes a tire have excellent carrying ability.
- Optimized tread profile design makes contact pressure distribution more uniform.
- Optimized tread recipe improves the applicability to bad road conditons.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB452	11ABB279	[E] 11.00R20	16	S150/ D147	K	TT	GL299T	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	16.0	20.2			
13GBB343	11ABB135	[E] 11.00R20	18	S152/ D149	J	TT	GL299T	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	16.0	20.2			

2013前进外贸轮胎-内页-ok.indd 38 2013-9-17 17:08:19

GL659A On & Off Road All-Position Radial

Product Features

- Strengthen carcass designing makes a tire a 30% improvement in carrying ability.
- Unique chafter with design patent makes a 30% improvement in blowout resistance.
- Strengthened crown structure makes a 30% improvement in the puncture resistance and blowout resistance at crown area.
- Deepened groove designing makes a tire service longer.
- Use double tread structure makes a tire generate lower heat and have superstrong durability.
- Optimized tread profile designing makes contact pressure distribution more uniform.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
TBA	TBA	[E] 10.00R20	16	S146/ D143	K	TT	GL659A	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DR08C	15.5	19.5			
13GBB611	11ABB372	[E] 10.00R20	18	S149/ D146	J	TT	GL659A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DR08C	15.5	19.5			
13GBB498	A1ABB334	[E] 11.00R20	18	S152/ D149	J	TT	GL659A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	16.0	20.2			
13GBB524	A1ABB349	[E] 12.00R20	18	S154/ D151	K	TT	GL659A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DR09C	16.5	20.8			
TBA	TBA	[E] 12.00R20	20	S156/ D153	J	TT	GL659A	313	12.3	1122	44.2	900	131	S4000/ D3650	S8820/ D8050	8.50	DR09C	16.5	20.8			
TBA	TBA	[E] 12R22.5	16	S150/ D147	M	TL	GL659A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	17.0	21.4			
13GBB613	11ABB374	[E] 12R22.5	18	S152/ D148	L	TL	GL659A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	17.0	21.4			
13GBB630	11ABB386	[E] 13R22.5	18	S154/ D150	K	TL	GL659A	320	12.6	1124	44.3	850	125	S3750/ D3350	S8270/ D7390	9.75	DR08	13.5	17.0			
13GBB735	A1ABB490	[E] 13R22.5	20	S156/ D150	J	TL	GL659A	320	12.6	1124	44.3	875	130	S4000/ D3350	S8820/ D7390	9.75	DR08	13.5	17.0			

2013前进外贸轮胎-内页-ok.indd 39 2013-9-17 17:08:21

GL662A On & Off Road All-Position Radial

Product Features

- Completely optimized structure and recipe designing makes a tire has better cost performance ratio.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.
- Excellent tear resistance under bad condition.
- Double tread structure makes a lower tire running temperature.
- Special pattern designing makes a tire get stronger traction.
- Lateral groove at shoulder area, which can strengthen heat dispersion,has higher durability.
- Completely new tread recipe makes wear and tear resistance reach the optimum compromise.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
TBA	11ABB459	10.00R20	18	S149/ D146	J	TT	GL662A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DR08C	15.5	19.5			
13GBB679	A1ABB435	11R22.5	14	S144/ D142	M	TL	GL662A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	15.3	19.3			
13GBB680	A1ABB436	E 11R22.5 SL	16	S146/ D143	M	TL	GL662A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	15.3	19.3	D	B	74
13GBB742	A1ABB496	E 11R22.5 SL	18	S148/ D145	L	TL	GL662A	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	15.3	19.3	D	B	74
13GBB772	11ABB444	E 12R22.5 SL	16	S150/ D147	M	TL	GL662A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	15.8	19.9	D	B	74
TBA	TBA	E 12R22.5 SL	18	S152/ D148	L	TL	GL662A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	15.8	19.9	D	B	74
13GBB656	A1ABB414	E 11R24.5	14	S146/ D143	M	TL	GL662A	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	15.3	19.3			
13GBB657	A1ABB415	E 11R24.5	16	S149/ D146	L	TL	GL662A	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	15.3	19.3			
13GBB792	11ABB458	13R22.5	18	S154/ D150	K	TL	GL662A	320	12.6	1124	44.3	850	125	S3750/ D3350	S8270/ D7390	9.75	DR08	15.0	18.9			
TBA	TBA	13R22.5	20	S156/ D150	J	TL	GL662A	320	12.6	1124	44.3	875	130	S4000/ D3350	S8820/ D7390	9.75	DR08	15.0	18.9			
13GBB696	A1ABB450	E 295/80R22.5 SL	16	S150/ D146	M	TL	GL662A	298	11.7	1044	41.1	800	115	S3350/ D3000	S7390/ D6610	9.00	DR08	15.8	19.9	C	C	74
13GBB678	A1ABB407	E 295/80R22.5 SL	18	S152/ D148	L	TL	GL662A	298	11.7	1044	41.1	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	15.8	19.9	C	C	74
13GBB697	A1ABB451	285/75R24.5	14	S144/ D141	M	TL	GL662A	283	11.1	1050	41.3	760	110	S2800/ D2575	S6175/ D5675	8.25	DR07	15.3	19.3			
13GBB698	A1ABB452	285/75R24.5	16	S147/ D144	L	TL	GL662A	283	11.1	1050	41.3	830	120	S3075/ D2800	S6780/ D6175	8.25	DR07	15.3	19.3			
13GBB726	A1ABB478	295/75R22.5	14	S144/ D141	M	TL	GL662A	298	11.7	1014	39.9	760	110	S2800/ D2575	S6175/ D5675	9.00	DR08	15.5	19.5			
13GBB727	A1ABB479	295/75R22.5	16	S146/ D143	L	TL	GL662A	298	11.7	1014	39.9	830	120	S3000/ D2725	S6610/ D6005	9.00	DR08	15.5	19.5			
13GBB692	11ABB413	E 315/80R22.5 SL	18	S154/ D150	M	TL	GL662A	312	12.3	1076	42.4	825	120	S3750/ D3350	S8270/ D7390	9.00	DR08	17.3	21.8	D	B	74
13GBB731	A1ABB485	E 315/80R22.5 SL	20	S156/ D150	L	TL	GL662A	312	12.3	1076	42.4	850	125	S4000/ D3750	S8820/ D7390	9.00	DR08	17.3	21.8	D	B	74

2013前进外贸轮胎-内页-ok.indd 40 2013-9-17 17:08:22

GL665A On & Off Road All-Position Radial

Product Features

- Double tread structure makes a lower tire running temperature.
- Deeper pattern makes a tire get longer service life.
- Special pattern designing makes a tire get stronger traction.
- Lateral groove at shoulder area, which can strengthen heat dispersion,has higher durability.
- Completely new tread recipe makes wear and tear resistance reach the optimum compromise.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB669	11ABB406	12.00R24	18	S158/ D155	K	TT	GL665A	323	12.4	1216	47.9	830	120	S4250/ D3875	S9370/ D8540	8.50	DG09C	19.0	23.9			
13GBB671	11ABB407	12.00R24	20	S160/ D157	J	TT	GL665A	323	12.4	1216	47.9	900	130	S4500/ D4125	S9920/ D9090	8.50	DG09C	19.0	23.9			
13GBB208	A1ABB145	E 295/80R22.5 S	16	S150/ D146	M	TL	GL665A	298	11.7	1044	41.1	800	115	S3350/ D3075	S7390/ D6780	9.00	DR08	17.5	22.0			
13GBB551	11ABB321	E 295/80R22.5 S	18	S152/ D148	L	TL	GL665A	298	11.7	1044	41.1	850	125	S3550/ D3250	S7830/ D7160	9.00	DR08	17.5	22.0			
13GBB188	A1ABB125	E 315/80R22.5 S	18	S154/ D150	M	TL	GL665A	312	12.3	1076	42.4	825	120	S3750/ D3350	S8270/ D7390	9.00	DR08	18.0	22.7			
13GBB189	A1ABB126	E 315/80R22.5 S	20	S156/ D150	L	TL	GL665A	312	12.3	1076	42.4	850	125	S4000/ D3750	S8820/ D7390	9.00	DR08	18.0	22.7			
13GBB360	A1ABB251	11R22.5	14	S144/ D142	M	TL	GL665A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	17.0	21.4			
13GBB538	A1ABB360	E 11R22.5 SL	16	S146/ D143	M	TL	GL665A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	17.0	21.4	D	B	74
13GBB744	A1ABB498	E 11R22.5 SL	18	S148/ D145	L	TL	GL665A	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	17.0	21.4	D	B	74
13GBB361	A1ABB252	E 12R22.5 S	16	S150/ D147	M	TL	GL665A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	17.5	22.0			
13GBB411	A1ABB286	E 12R22.5 S	18	S152/ D148	L	TL	GL665A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	17.5	22.0			
13GBB396	A1ABB474	E 13R22.5 SL	18	S154/ D150	K	TL	GL665A	320	12.6	1124	44.3	850	125	S3750/ D3350	S8270/ D7390	9.75	DR08	17.5	22.0	D	A	75
13GBB624	A1ABB381	E 13R22.5 SL	20	S156/ D150	J	TL	GL665A	320	12.6	1124	44.3	875	130	S4000/ D3350	S8820/ D7390	9.75	DR08	17.5	22.0	D	A	75

2013前进外贸轮胎-内页-ok.indd 41 2013-9-17 17:08:23

GL671A On & Off Road All-Position Radial

Product Features

- Three central ""Z"" grooves and unique groove shape designing gurantee a tire have excellent traction and brake performance.
- Unique recipe designing guarantees a tire have excellent tear resistance.
- Bigger lateral groove at shoulder area guarantees better traction and grip.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB489	11ABB290	6.50R16	12	S110/ D105	L	TT	GL671A	185	7.3	750	29.5	670	97	S1060/ D925	S2340/ D2040	5.50	CJ01	10.5	13.2			
13GBB490	11ABB291	7.00R16	14	S118/ D114	L	TT	GL671A	200	7.9	782	30.8	770	110	S1320/ D1180	S2900/ D2600	5.50	DG04C	11.0	13.9			
13GBB345	11ABB137	E 7.50R16 S	14	S122/ D118	L	TT	GL671A	215	8.5	805	31.7	770	110	S1500/ D1320	S3305/ D2900	6.00	DG04C	11.0	13.9			
13GBB346	11ABB138	E 8.25R16 S	14	S126/ D122	L	TT	GL671A	235	9.3	855	33.7	670	97	S1700/ D1500	S3745/ D3305	6.50	DG05C	12.0	15.1			
13GBB420	11ABB252	E 8.25R16 S	16	S128/ D124	K	TT	GL671A	235	9.3	855	33.7	770	110	S1800/ D1600	S3970/ D3525	6.50	DG05C	12.0	15.1			
13GBB369	11ABB240	E 7.50R20 S	14	S130/ D128	K	TT	GL671A	215	8.5	935	36.8	830	120	S1900/ D1800	S4190/ D3970	6.00	DG06C	13.0	16.4			
13GBB349	11ABB141	E 8.25R20 S	14	S136/ D134	K	TT	GL671A	236	9.3	974	38.3	830	120	S2240/ D2120	S4940/ D4675	6.50	DG06C	14.0	17.6			
13GBB428	11ABB260	E 8.25R20 S	16	S139/ D137	J	TT	GL671A	236	9.3	974	38.3	930	135	S2430/ D2300	S5355/ D5070	6.50	DG06C	14.0	17.6			
13GBB273	A1ABB209	E 9.00R20 S	16	S144/ D142	K	TT	GL671A	259	10.2	1019	40.1	900	130	S2800/ D2650	S6175/ D5840	7.00	DG07C	15.0	18.9			
13GBB294	A1ABB215	E 10.00R20 S	16	S146/ D143	K	TT	GL671A	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	16.0	20.2			
13GBB295	A1ABB216	E 10.00R20 S	18	S149/ D146	J	TT	GL671A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	16.0	20.2			
13GBB344	11ABB136	E 11.00R20 S	18	S152/ D149	J	TT	GL671A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	16.5	20.8			
13GBB276	A1ABB142	E 12.00R20 S	18	S154/ D151	K	TT	GL671A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	17.0	21.4			
13GBB462	11ABB147	E 12.00R20 S	20	S156/ D153	J	TT	GL671A	313	12.3	1122	44.2	900	130	S4000/ D3650	S8820/ D8050	8.50	DG09C	17.0	21.4			
13GBB185	A1ABB119	11R22.5	14	S144/ D142	M	TL	GL671A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	16.0	20.2			
13GBB187	A1ABB121	E 11R22.5 S	16	S146/ D143	M	TL	GL671A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	16.0	20.2			
13GBB307	11ABB118	E 11R24.5 S	14	S146/ D143	M	TL	GL671A	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	16.5	20.8			
13GBB308	11ABB119	E 11R24.5 S	16	S149/ D146	L	TL	GL671A	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	16.5	20.8			
13GBB306	11ABB246	E 12R22.5 S	16	S150/ D147	M	TL	GL671A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	16.5	20.8			
TBA	TBA	E 12R22.5 S	18	S152/ D148	L	TL	GL671A	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	16.5	20.8			
13GBB236	A1ABB266	E 13R22.5 S	18	S154/ D150	K	TL	GL671A	320	12.6	1124	44.3	850	125	S3750/ D3350	S8270/ D7390	9.75	DR08	17.0	21.4			
13GBB542	A1ABB361	E 13R22.5 S	20	S156/ D150	J	TL	GL671A	320	12.6	1124	44.3	875	130	S4000/ D3350	S8820/ D7390	9.75	DR08	17.0	21.4			

2013前进外贸轮胎-内页-ok.indd 42 2013-9-17 17:08:25

GL679A On & Off Road All-Position Radial

Product Features

- Excellent recipe makes a tire has superstrong abrasion resistance.
- Broken line circumferential groove designing provides good operational property and enough traction.
- Lateral small and narrow grooves effectively improve a tire's wet skid resistance and largely decrease the irregular wear of the tread.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB494	11ABB295	[E] 7.50R16	14	S122/ D118	L	TT	GL679A	215	8.5	805	31.7	770	110	S1500/ D1320	S3305/ D2900	6.00	DG04C	11.5	14.5			
13GBB347	11ABB139	[E] 8.25R16	14	S126/ D122	L	TT	GL679A	235	9.3	855	33.7	670	97	S1700/ D1500	S3745/ D3305	6.50	DG05C	12.0	15.1			
13GBB423	11ABB255	[E] 8.25R16	16	S128/ D124	K	TT	GL679A	235	9.3	855	33.7	770	110	S1800/ D1600	S3970/ D3525	6.50	DG05C	12.0	15.1			

2013前进外贸轮胎-内页-ok.indd 43 2013-9-17 17:08:25

GL682A On & Off Road All-Position Radial

Product Features

- Three central ""Z"" grooves and unique groove shape designing gurantee a tire have excellent traction and brake performance.
- Unique recipe designing guarantees a tire have excellent tear resistance.
- Bigger lateral groove at shoulder area guarantees better traction and grip.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
TBA	TBA	11.00R20	16	S150/ D147	K	TT	GL682A	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	16.5	20.8			
TBA	A1ABB484	11.00R20	18	S152/ D149	J	TT	GL682A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	16.5	20.8			
TBA	11ABB456	12.00R20	16	S152/ D149	K	TT	GL682A	313	12.3	1122	44.2	760	110	S3550/ D3250	S7830/ D7160	8.50	DG09C	17.0	21.4			
TBA	11ABB419	12.00R20	18	S154/ D151	K	TT	GL682A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	17.0	21.4			
TBA	11ABB420	12.00R20	20	S156/ D153	J	TT	GL682A	313	12.3	1122	44.2	900	130	S4000/ D3650	S8820/ D8050	8.50	DG09C	17.0	21.4			

2013前进外贸轮胎-内页-ok.indd 44 2013-9-17 17:08:26

GL689A On & Off Road All-Position Radial

Product Features

- Deeper pattern makes a tire service longer.
- Special tread pattern designing makes a stronger tire traction.
- Completely new tread recipe makes wear and tear resistance get optimum compromise.
- Open shoulder designing makes a tire adapt various mixed road conditions.
- Optimized crown designing makes a tire have good puncture resistance.
- Strengthened carcass designing makes a tire have overlong service life and can be retreaded several times.
- Strengthened chafer designing makes a tire have excellent carrying property.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB644	11ABB393	7.50R16	14	S122/ D118	L	TT	GL689A	215	8.5	805	31.7	770	110	S1500/ D1320	S3305/ D2900	6.00	DG04C	15.0	18.9			
13GBB643	A1ABB394	8.25R16	16	S128/ D124	K	TT	GL689A	235	9.3	855	33.7	770	110	S1800/ D1600	S3970/ D3525	6.50	DG05C	15.0	18.9			
13GBB143	11ABB073	E 9.00R20 S	16	S144/ D142	K	TT	GL689A	259	10.2	1019	40.1	900	130	S2800/ D2650	S6175/ D5840	7.00	DG07C	17.0	21.4			
TBA	TBA	E 10.00R20 S	16	S146/ D143	K	TT	GL689A	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	17.5	22.0			
13GBB144	11ABB074	E 10.00R20 S	18	S149/ D146	J	TT	GL689A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	17.5	22.0			
13GBB457	11ABB281	E 11.00R20 S	16	S150/ D147	K	TT	GL689A	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	18.0	22.7			
13GBB142	11ABB072	E 11.00R20 S	18	S152/ D149	J	TT	GL689A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	18.0	22.7			
13GBB141	11ABB071	E 12.00R20 S	18	S154/ D151	K	TT	GL689A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	18.5	23.3			
13GBB464	11ABB099	E 12.00R20 S	20	S156/ D153	J	TT	GL689A	313	12.3	1122	44.2	900	130	S4000/ D3650	S8820/ D8050	8.50	DG09C	18.5	23.3			
13GBB487	A1ABB331	E 385/65R22.5 S L	18	158	L	TL	GL689A	389	15.3	1072	42.2	850	125	S4250	S9370	11.75		18.5	23.3	E	B	76
13GBB566	11ABB336	E 385/65R22.5 S L	20	160	K	TL	GL689A	389	15.3	1072	42.2	900	130	S4500	S9920	11.75		18.5	23.3	E	B	76
13GBB768	A1ABB503	425/65R22.5	20	165	K	TL	GL689A	430	16.9	1124	44.3	825	120	5150	11400	12.25		18.5	23.3			
13GBB769	A1ABB505	445/65R22.5	20	169	K	TL	GL689A	444	17.5	1150	45.3	900	130	5800	12800	13.00		18.5	23.3			

2013前进外贸轮胎-内页-ok.indd 45 2013-9-17 17:08:27

GL691A On & Off Road All-Position Radial

Product Features

- Unique corner design of the groove can avoid irregular wear of the pattern.
- Unique groove bottom makes a tire have good self-clean property, which can effectively protect crown.
- Larger lateral groove at shoulder area guarantees a tire have better traction and grip.
- Optimized belt structure designing strengthens the rigidity and flex at crown, which can guarantes the uniform wear of the tire.
- Specialized designed recipe guarantees a tire's tear resistance and cost performance ratio at complex condition.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB435	11ABB263	12.00R24	18	S158/ D155	K	TT	GL691A	323	12.4	1216	47.9	830	120	S4250/ D3875	S9370/ D8540	8.50	DG09C	16.0	20.2			
13GBB437	11ABB265	12.00R24	20	S160/ D157	J	TT	GL691A	323	12.4	1216	47.9	900	130	S4500/ D4125	S9920/ D9090	8.50	DG09C	16.0	20.2			

2013前进外贸轮胎-内页-ok.indd 46 2013-9-17 17:08:28

GL697A On & Off Road All-Position Radial

Product Features

- Strengthen carcass designing makes a tire a 30% improvement in carrying ability.
- Unique chafter with design patent makes a 30% improvement in blowout resistance.
- Strengthened crown structure makes a 30% improvement in the puncture resistance and blowout resistance at crown area.
- Deepened groove designing makes a tire service longer.
- Widered tread cap design makes a sronger tire traction.
- Streamline formed groove design guarantees a good tire pattern self-clean property under mining and other conditions.
- Thick and strong block design provides strong traction.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB559	11ABB329	7.50R16	14	S122/ D118	L	TT	GL697A	215	8.5	805	31.7	770	110	S1500/ D1320	S3305/ D2900	6.00	DG04C	15.5	19.5			
13GBB519	11ABB307	8.25R16	14	S126/ D122	L	TT	GL697A	235	9.3	855	33.7	670	97	S1700/ D1500	S3745/ D3305	6.50	DG05C	16.0	20.2			
13GBB521	11ABB305	8.25R16	16	S128/ D124	K	TT	GL697A	235	9.3	855	33.7	770	110	S1800/ D1600	S3970/ D3525	6.50	DG05C	16.0	20.2			
13GBB615	11ABB376	[E] 8.25R20	16	S139/ D137	J	TT	GL697A	236	9.3	974	38.3	930	135	S2430/ D2300	S5355/ D5070	6.50	DG06C	16.5	20.8			
13GBB467	11ABB284	[E] 11.00R20	18	S152/ D149	J	TT	GL697A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	19.5	24.6			
13GBB485	A1ABB329	[E] 12.00R20	18	S154/ D151	K	TT	GL697A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	19.5	24.6			

2013前进外贸轮胎-内页-ok.indd 47 2013-9-17 17:08:29

GL656D On & Off Road Drive-Position Radial

Product Features

- Completely optimized structure and recipe designing makes a tire has better cost performance ratio.
- The most recent low rolling resistance designing makes the fuel consumption of the vehicle significantly decrease and the cost of the truckload effectively decrease.
- Use the double tread structure makes a tire generate less heat.
- Optimized pattern shape designing gurantees a tire has excellent wet skid resistance.
- Unidirectional pattern designing and unique block designing provide excellent driving properties.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB773	11ABB445	11R22.5	16	S146/ D143	M	TL	GL656D	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	24.5	30.9			
13GBB774	11ABB446	11R22.5	18	S148/ D145	L	TL	GL656D	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	24.5	30.9			
13GBB783	A1ABB513	11R24.5	14	S146/ D143	M	TL	GL656D	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	24.5	30.9			
13GBB784	A1ABB514	11R24.5	16	S149/ D146	L	TL	GL656D	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	24.5	30.9			

2013前进外贸轮胎-内页-ok.indd 48 2013-9-17 17:08:34

GL663D On & Off Road Drive-Position Radial

Product Features

- Wide lateral groove designing makes a tire has strong traction under soft road surface.
- Deeper pattern makes a tire get longer service life.
- Special pattern designing makes a tire has good applicability under different road surfaces.
- Completely new tread recipe makes wear and tear resistance reach the optimum compromise.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB539	11ABB316	7.00R16	14	S118/ D114	L	TT	GL663D	200	7.9	782	30.8	770	110	S1320/ D1180	S2900/ D2600	5.50	DG04C	15.0	18.9			
13GBB492	11ABB293	E 7.50R16	14	S122/ D118	L	TT	GL663D	215	8.5	805	31.7	770	110	S1500/ D1320	S3305/ D2900	6.00	DG04C	15.5	19.5			
13GBB495	11ABB296	E 8.25R16	14	S126/ D122	L	TT	GL663D	235	9.3	855	33.7	670	97	S1700/ D1500	S3745/ D3305	6.50	DG05C	16.0	20.2			
13GBB419	11ABB251	E 8.25R16	16	S128/ D124	L	TT	GL663D	235	9.3	855	33.7	770	110	S1800/ D1600	S3970/ D3525	6.50	DG05C	16.0	20.2			
13GBB182	11ABB092	E 8.25R20	14	S136/ D134	K	TT	GL663D	236	9.3	974	38.3	830	120	S2240/ D2120	S4940/ D4675	6.50	DG06C	16.5	20.8			
13GBB427	11ABB259	E 8.25R20	16	S139/ D137	J	TT	GL663D	236	9.3	974	38.3	930	135	S2430/ D2300	S5355/ D5070	6.50	DG06C	16.5	20.8			
13GBB178	11ABB083	E 9.00R20	16	S144/ D142	K	TT	GL663D	259	10.2	1019	40.1	900	130	S2800/ D2650	S6175/ D5840	7.00	DG07C	18.5	23.3			
TBA	TBA	E 10.00R20	16	S146/ D143	K	TT	GL663D	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DR08C	19.0	23.9			
13GBB351	11ABB143	E 10.00R20	18	S149/ D146	J	TT	GL663D	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DR08C	19.0	23.9			
13GBB183	11ABB093	E 11.00R20	18	S152/ D149	J	TT	GL663D	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	19.5	24.6			
13GBB382	A1ABB285	E 12.00R20	18	S154/ D151	K	TT	GL663D	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	19.5	24.6			
13GBB690	11ABB411	E 13R22.5 SL	18	S154/ D150	K	TL	GL663D	320	12.6	1124	44.3	850	125	S3750/ D3350	S8270/ D7390	9.75	DR08	19.5	24.6	D	C	76
TBA	TBA	E 13R22.5 SL	20	S156/ D150	J	TL	GL663D	320	12.6	1124	44.3	875	130	S4000/ D3350	S8820/ D7390	9.75	DR08	19.5	24.6	D	C	76

2013前进外贸轮胎-内页-ok.indd 49 2013-9-17 17:08:36

GL672D On & Off Road Drive-Position Radial

Product Features

- Thick and strong ""Z"" pattern and Wider lateral pattern at center makes a tire have good operational property under bad road condidion.
- Strengthened shoulder pattern at side area makes a tire have stronger traction and grip.
- Eliminate sharp points in pattern designing which improves a tire's cutting and tear resistance.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB491	11ABB292	7.00R16	14	S118/ D114	L	TT	GL672D	200	7.9	782	30.8	770	110	S1320/ D1180	S2900/ D2600	5.50	DG04C	14.0	17.6			
13GBB493	11ABB294	E 7.50R16	14	S122/ D118	L	TT	GL672D	215	8.5	805	31.7	770	110	S1500/ D1320	S3305/ D2900	6.00	DG04C	14.5	18.3			
13GBB496	11ABB297	E 8.25R16	14	S126/ D122	L	TT	GL672D	235	9.3	855	33.7	670	97	S1700/ D1500	S3745/ D3305	6.50	DG05C	15.0	18.9			
13GBB422	11ABB254	E 8.25R16	16	S128/ D124	K	TT	GL672D	235	9.3	855	33.7	770	110	S1800/ D1600	S3970/ D3525	6.50	DG05C	15.0	18.9			
13GBB123	11ABB059	E 8.25R20	14	S136/ D134	K	TT	GL672D	236	9.3	974	38.3	830	120	S2240/ D2120	S4940/ D4675	6.50	DG06C	15.0	18.9			
13GBB430	11ABB262	E 8.25R20	16	S139/ D137	J	TT	GL672D	236	9.3	974	38.3	930	135	S2430/ D2300	S5355/ D5070	6.50	DG06C	15.0	18.9			
13GBB274	A1ABB210	E 9.00R20	16	S144/ D142	K	TT	GL672D	259	10.2	1019	40.1	900	130	S2800/ D2650	S6175/ D5840	7.00	DG07C	15.5	19.5			
13GBB296	A1ABB217	E 10.00R20	16	S146/ D143	K	TT	GL672D	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	16.5	20.8			
13GBB297	A1ABB218	E 10.00R20	18	S149/ D146	J	TT	GL672D	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	16.5	20.8			
13GBB005	11ABB005	E 11.00R20	16	S150/ D147	K	TT	GL672D	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	17.0	21.4			
13GBB537	11ABB313	E 11.00R20	18	S152/ D149	J	TT	GL672D	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	17.0	21.4			

2013前进外贸轮胎-内页-ok.indd 50 2013-9-17 17:08:37

GL681D On & Off Road Drive-Position Radial

Product Features

- Thick and strong blocks and Wider lateral grooves provide strong traction and grip.
- Optimized small and narrow grooves provide better wet skid resistance.
- Lateral small and narrow grooves improve a tire's irregular wear resistance and travelling stability.
- Patterns which are deeper than GL672D provide high abrasion resistance and longer service life.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB156	11ABB075	[E] 9.00R20	16	S144/ D142	K	TT	GL681D	259	10.2	1019	40.1	900	130	S2800/ D2650	S6175/ D5840	7.00	DG07C	17.0	21.4			
TBA	TBA	[E] 10.00R20	16	S146/ D143	K	TT	GL681D	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	18.0	22.7			
13GBB124	11ABB060	[E] 10.00R20	18	S149/ D146	J	TT	GL681D	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	18.0	22.7			
TBA	TBA	[E] 11.00R20	16	S150/ D147	K	TT	GL681D	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	18.5	23.3			
13GBB125	11ABB061	[E] 11.00R20	18	S152/ D149	J	TT	GL681D	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	18.5	23.3			
13GBB126	11ABB236	[E] 12.00R20	18	S154/ D151	K	TT	GL681D	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	19.0	23.9			
TBA	TBA	[E] 12.00R20	20	S156/ D153	J	TT	GL681D	313	12.3	1122	44.2	900	130	S4000/ D3650	S8820/ D8050	8.50	DG09C	19.0	23.9			

2013前进外贸轮胎-内页-ok.indd 51 2013-9-17 17:08:37

GL687D On & Off Road Drive-Position Radial

Product Features

- Use undirectional pattern desinging.
- Deepened groove designing makes a 10% improvement in service life.
- Wider tire cap designing makes traction stronger.
- Streamline formed groove designing guarantees a tire has good pattern self-clean property under working area and other conditions.
- Thick and strong block designing provides strong traction."

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB476	11ABB287	E 9.00R20	16	S144/ D142	K	TT	GL687D	259	10.2	1019	40.1	900	130	S2800/ D2650	S6175/ D5840	7.00	DG07C	18.5	23.3			
13GBB479	A1ABB325	E 10.00R20	16	S146/ D143	K	TT	GL687D	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	19.0	23.9			
13GBB482	A1ABB328	E 10.00R20	18	S149/ D146	J	TT	GL687D	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	19.0	23.9			
TBA	TBA	E 11.00R20 SL	16	S150/ D147	K	TT	GL687D	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	19.5	24.6	E	B	76
13GBB058	11ABB049	E 11.00R20 SL	18	S152/ D149	J	TT	GL687D	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	19.5	24.6	E	B	76
13GBB127	11ABB063	E 12.00R20 SL	18	S154/ D151	K	TT	GL687D	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	19.5	24.6	D	C	76
TBA	TBA	E 12.00R20 SL	20	S156/ D153	J	TT	GL687D	313	12.3	1122	44.2	900	130	S4000/ D3650	S8820/ D8050	8.50	DG09C	19.5	24.6	D	C	76
13GBB235	A1ABB171	E 12R22.5 S	16	S150/ D147	M	TL	GL687D	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	19.5	24.6			
TBA	TBA	E 12R22.5 S	18	S152/ D148	L	TL	GL687D	300	11.8	1084	42.7	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	19.5	24.6			
TBA	TBA	E 13R22.5	18	S154/ D150	K	TL	GL687D	320	12.6	1124	44.3	850	125	S3750/ D3350	S8270/ D7390	9.75	DR08	19.5	24.6			
TBA	TBA	E 13R22.5	20	S156/ D150	J	TL	GL687D	320	12.6	1124	44.3	875	130	S4000/ D3350	S8820/ D7390	9.75	DR08	19.5	24.6			
13GBB270	A1ABB206	E 315/80R22.5 SL	18	S154/ D150	L	TL	GL687D	312	12.3	1076	42.4	825	120	S3750/ D3350	S8270/ D7390	9.00	DR08	21.0	26.5	E	B	76
13GBB278	11ABB107	E 315/80R22.5 SL	20	S156/ D150	G	TL	GL687D	312	12.3	1076	42.4	850	125	S4000/ D3750	S8820/ D7390	9.00	DR08	21.0	26.5	E	B	76

2013前进外贸轮胎-内页-ok.indd 52 2013-9-17 17:08:38

GL670T On & Off Road Trailer-Position Radial

Product Features

- Open shoulder designing makes a tire adapt the transportation under various mixed road conditons.
- Good heat dispersion makes a tire have excellent durability.
- Excellent recipe makes a tire have superstrong abrasion resistance.
- Optimized crown designing makes a tire have good puncture resistance.
- Strengthened carcass designing makes a tire have overlong service life and can be retreaded several times.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB636	A1ABB387	^{E}385/65R22.5 ^{S,L}	18	158	L	TL	GL670T	389	15.3	1072	42.2	850	125	S4250	S9370	11.75		17.0	21.4	C	D	76
13GBB639	A1ABB390	^{E}385/65R22.5 ^{S,L}	20	160	K	TL	GL670T	389	15.3	1072	42.2	900	130	S4500	S9920	11.75		17.0	21.4	C	D	76
13GBB641	A1ABB392	^{E}425/65R22.5 ^{S,L}	20	165	K	TL	GL670T	430	16.9	1124	44.3	825	120	5150	11400	12.25		17.0	21.4	C	D	76
13GBB642	A1ABB393	^{E}445/65R22.5 ^{S,L}	20	169	K	TL	GL670T	444	17.5	1150	45.3	900	130	5800	12800	13.00		17.0	21.4	C	D	76

2013前进外贸轮胎-内页-ok.indd 53 2013-9-17 17:08:39

GL718D Severe Snow Condition Drive-Position Radial

Product Features

- All-weather highway drive tyre
- Serrated sipes help deliver exceptional traction and excellent wear
- 25/32nds original tread depth
- Wide open shoulder grooves deliver additional traction balanced with tread life
- Unidirectional pattern design provide excellent driving performance.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB779	A1ABB508	295/80R22.5	16	S150/ D146	M	TL	GL718D	298	11.7	1044	41.1	800	115	S3350/ D3000	S7390/ D6610	9.00	DR08	20.0	25.2			
13GBB780	A1ABB509	295/80R22.5	18	S152/ D148	L	TL	GL718D	298	11.7	1044	41.1	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	20.0	25.2			

2013前进外贸轮胎-内页-ok.indd 54 2013-9-17 17:08:57

GL828A Urban bus All-Position Radial

Product Features

- Self-clean technology of the groove and extra deep undertread designing makes a tire have excellent self-clean property and puncture resistance, so as to provide optimum safety guarantee for a tire.
- Optimized groove shape designing makes a tire have more excellent water resistance and wet skid resistance.
- Extra deep pattern can get longer service life.
- Thicken the sidewall designing can effectively protect the sidewall from scaping,so as to provide sidewall optimum protection.
- The use of special tread recipe makes rolling resistance lower and fuel consumption lower.
- Superstrong chafer with design patent provides a tire optimum carrying capacity and resistance to failure.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB335	11ABB129	11R22.5	14	S144/ D142	M	TL	GL828A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	20.0	25.2			
13GBB336	11ABB130	E 11R22.5 SL	16	S146/ D143	J	TL	GL828A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	20.0	25.2	D	B	74
13GBB745	A1ABB499	E 11R22.5 SL	18	S148/ D145	G	TL	GL828A	279	11.0	1050	41.3	850	125	S3150/ D2900	S6940/ D6395	8.25	DR07	20.0	25.2	D	B	74
13GBB531	11ABB310	E 275/70R22.5 SL	16	S144/ D141	J	TL	GL828A	276	10.9	958	37.7	830	120	S2800/ D2575	S6175/ D5675	8.25	DR07	20.0	25.2	D	C	76
13GBB758	11ABB433	E 275/70R22.5 SL	18	S148/ D145	G	TL	GL828A	276	10.9	958	37.7	900	130	S3150/ D2900	S6940/ D6395	8.25	DR07	20.0	25.2	D	C	76

2013前进外贸轮胎-内页-ok.indd 55 2013-9-17 17:08:58

GL908A Off Road All-Position Radial

Product Features

- Special tread pattern design, higher traction on mining road.
- Extra deep pattern,longer service life of tire.
- Extra deep undertread design, best protect the belts and carcass when tire runs on mining road.
- Special stone rejector designed at shoulder and thicker sidewall design,best protection due to prevent stone from inserting between the sidewalls in case of dual tires effectively.
- Superstrong patent chafer provides a tire with optimal carrying capacity and resistance to bead blowout.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB581	11ABB350	7.50R16	14	S122/ D118	L	TT	GL908A	215	8.5	805	31.7	770	110	S1500/ D1320	S3305/ D2900	6.00	DG04C	20.5	25.8			
13GBB579	11ABB352	8.25R16	16	S128/ D124	K	TT	GL908A	235	9.3	855	33.7	770	110	S1800/ D1600	S3970/ D3525	6.50	DG05C	21.0	26.5			
13GBB607	A1ABB372	8.25R20	14	S136/ D134	K	TT	GL908A	236	9.3	974	38.3	830	120	S2240/ D2120	S4940/ D4675	6.50	DG06C	21.0	26.5			
13GBB609	A1ABB374	8.25R20	16	S139/ D137	J	TT	GL908A	236	9.3	974	38.3	930	135	S2430/ D2300	S5355/ D5070	6.50	DG06C	21.0	26.5			
13GBB791	11ABB457	9.00R20	16	S144/ D142	F	TT	GL908A	259	10.2	1019	40.1	900	130	S2800/ D2650	S6175/ D5840	7.00	DG07C	21.5	27.1			
13GBB486	A1ABB330	10.00R20	18	S149/ D146	J	TT	GL908A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	24.0	30.2			
13GBB304	11ABB115	11.00R20	18	S152/ D149	J	TT	GL908A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	25.0	31.5			
13GBB395	A1ABB311	12.00R20	18	S154/ D151	K	TT	GL908A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	25.0	31.5			
13GBB781	A1ABB511	295/80R22.5	16	S150/ D146	K	TL	GL908A	298	11.7	1044	41.1	800	115	S3350/ D3000	S7390/ D6610	9.00	DR08	20.0	25.2			
13GBB782	A1ABB512	295/80R22.5	18	S152/ D148	J	TL	GL908A	298	11.7	1044	41.1	850	125	S3550/ D3150	S7830/ F6940	9.00	DR08	20.0	25.2			

2013前进外贸轮胎-内页-ok.indd 56 2013-9-17 17:08:59

GL909A Off Road All-Position Radial

Product Features

- Special tread pattern design, higher traction on mining road.
- Unique groove design, higher ability of self-clean without derit into it completely.
- Extra deep pattern,longer service life of tire.
- Extra deep undertread designing makes belts and carcass get optimum protection when tire is running on mining road.
- Superstrong patent chafer provides a tire optimum carrying capacity and resistance to bead blowout.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB645	A1ABB398	11R22.5	14	S144/ D142	M	TL	GL909A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	23.5	29.6			
13GBB605	A1ABB370	11R22.5	16	S146/ D143	G	TL	GL909A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	23.5	29.6			
13GBB563	11ABB333	12R22.5	16	S150/ D147	G	TL	GL909A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	25.5	32.1			
13GBB650	A1ABB401	11R24.5	14	S146/ D143	M	TL	GL909A	279	11.0	1104	43.5	720	105	S3000/ D2800	S6610/ D6005	8.25	DR08	23.0	29.0			
13GBB651	A1ABB402	11R24.5	16	S149/ D146	L	TL	GL909A	279	11.0	1104	43.5	830	120	S3250/ D3000	S7160/ D6610	8.25	DR08	23.0	29.0			
13GBB633	A1ABB384	11.00R20	18	S152/ D149	F	TT	GL909A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	25.0	31.5			
13GBB465	11ABB283	12.00R24	☆☆☆/18	S158/ D155	F	TT	GL909A	323	12.7	1256	49.4	830	120	S4250/ D3875	S9370/ D8540	8.50	DG09C	31.0	39.0			

2013前进外贸轮胎-内页-ok.indd 57 2013-9-17 17:09:00

GL912A Off Road All-Position Radial

Product Features

- Special tread pattern design, higher traction on mining road.
- Extra deep pattern,longer service life of tire.
- Extra deep undertread design, best protect the belts and carcass when tire runs on mining road.
- Special stone rejector design at shoulder and thicker sidewall design,best protection due to prevent stone from inserting between the sidewalls in case of dual tires.
- Superstrong patent chafer provides a tire with optimal carrying capacity and resistance to bead blowout.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB466	11ABB349	11.00R20	18	S152/ D149	J	TT	GL912A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	25.0	31.5			
13GBB547	11ABB318	12.00R20	18	S154/ D151	K	TT	GL912A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	25.0	31.5			
TBA	TBA	12.00R20	20	S156/ D153	J	TT	GL912A	313	12.3	1122	44.2	900	130	S4000/ D3650	S8820/ D8050	8.50	DG09C	25.0	31.5			

2013前进外贸轮胎-内页-ok.indd 58 2013-9-17 17:09:01

GL918A Off Road All-Position Radial

Product Features

- Completely new profile designing makes a tire have superhigh cost performance ratio.
- Completely new recipe designing effectively lowers heat generation and improves a tire's service life on mixed road surface.
- Optimized undertread designing makes the belts and carcass get optimum protection when the tire is running on complex road.
- Superstrong chafer with design patent provides a tire optimum carrying capacity and resistance to failure.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB716	A1ABB472	11.00R20	18	S152/ D149	J	TT	GL918A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	22.5	28.3			
13GBB721	11ABB416	12.00R20	18	S154/ D151	K	TT	GL918A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	22.5	28.3			

2013前进外贸轮胎-内页-ok.indd 59 2013-9-17 17:09:02

GL969A Off Road All-Position Radial

Product Features

- Special pattern designing makes a tire get stronger traction.
- Deeper pattern makes a tire get longer service life.
- Thick and strong pattern designing makes a tire have good applicability under different road surfaces.
- Special groove bottom protection makes it not easy to puncture when the tire is running.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB147	11ABB066	9.00R20	16	S144/ D142	K	TT	GL969A	259	10.2	1019	40.1	900	130	S2800/ D2650	S6175/ D5840	7.00	DG07C	18.5	23.3			
TBA	TBA	10.00R20	16	S146/ D143	K	TT	GL969A	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	19.0	23.9			
13GBB148	11ABB067	10.00R20	18	S149/ D146	J	TT	GL969A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	19.0	23.9			
TBA	TBA	11.00R20	16	S150/ D147	K	TT	GL969A	293	11.5	1085	42.7	830	120	S3350/ D3075	S7390/ D6780	8.00	DG09C	19.5	24.6			
13GBB146	11ABB065	11.00R20	18	S152/ D149	J	TT	GL969A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	19.5	24.6			
13GBB145	11ABB064	12.00R20	18	S154/ D151	K	TT	GL969A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	20.0	25.2			

2013前进外贸轮胎-内页-ok.indd 60 2013-9-17 17:09:03

GL992A Off Road All-Position Radial

Product Features

- Completely new tread recipe design for cutting resistance.
- Thick and strong block design provides strong traction.
- Optimized groove design makes tread have excellent self-clean property.
- Deepened tread pattern provides longer service life.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
TBA	TBA	10.00R20	16	S146/ D143	K	TT	GL992A	275	10.8	1052	41.4	830	120	S3000/ D2725	S6610/ D6005	7.50	DG08C	19.0	23.9			
13GBB510	11ABB298	10.00R20	18	S149/ D146	J	TT	GL992A	275	10.8	1052	41.4	930	135	S3250/ D3000	S7160/ D6610	7.50	DG08C	19.0	23.9			
13GBB473	A1ABB321	11.00R20	18	S152/ D149	J	TT	GL992A	293	11.5	1085	42.7	930	135	S3550/ D3250	S7830/ D7160	8.00	DG09C	19.5	24.6			
13GBB530	A1ABB355	12.00R20	18	S154/ D151	K	TT	GL992A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50	DG09C	20.0	25.2			
13GBB310	11ABB121	11R22.5	14	S144/ D142	M	TL	GL992A	279	11.0	1050	41.3	720	105	S2800/ D2650	S6175/ D5840	8.25	DR07	19.0	23.9			
13GBB309	11ABB120	11R22.5	16	S146/ D143	M	TL	GL992A	279	11.0	1050	41.3	830	120	S3000/ D2725	S6610/ D6005	8.25	DR07	19.0	23.9			
13GBB416	A1ABB291	12R22.5	16	S150/ D147	M	TL	GL992A	300	11.8	1084	42.7	850	125	S3350/ D3075	S7390/ D6780	9.00	DR08	19.5	24.6			
13GBB237	A1ABB173	13R22.5	18	S154/ D150	K	TL	GL992A	320	12.6	1124	44.3	850	125	S3750/ D3350	S8270/ D7390	9.75	DR08	19.5	24.6			
13GBB544	A1ABB363	13R22.5	20	S156/ D150	J	TL	GL992A	320	12.6	1124	44.3	875	130	S4000/ D3350	S8820/ D7390	9.75	DR08	19.5	24.6			

2013前进外贸轮胎-内页-ok.indd 61 2013-9-17 17:09:04

GL073A Military Service All-Position Radial

Product Features

- Each pattern is relatively thick and strong and they are interconnected by reinforcing ribs, which makes a tire have better toughness.
- Wide and deep lateral groove makes a tire have strong traction and grip.
- Round shoulder profile makes a tire have excellent cross-country property.
- Prominent kerbing rib designing of side direction can prevent sidewall from impacting and scratching of external force.

Recommended Vehicle Types & Position

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Load Index	Speed Symbol	Type	Pattern	Section Width (mm)	Section Width (in.)	Overall Diam. (mm)	Overall Diam. (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth(mm)	Tread Depth(32nds)	Energy efficiency class	Wet grip class	Rolling noise class
13GBB233	A1ABB169	E 12.00R20 S	18	S154/ D151	K	TL	GL073A	313	12.3	1122	44.2	830	120	S3750/ D3450	S8270/ D7610	8.50		18.0	22.7			
TBA	A1ABB346	12.00R20	20	S156/ D153	J	TL	GL073A	313	12.3	1122	44.2	900	130	S4000/ D3650	S8820/ D8050	8.50		18.0	22.7			
13GBB074	11ABB026	E 14.00R20 S	18	S161/ D158	J	TT	GL073A	375	14.8	1240	48.8	690	100	S4625/ D4250	S10200/ D9370	10.00	DG09C	20.0	25.2			
13GBB046	11ABB038	E 14.00R20 S	20	S164/ D161	G	TT	GL073A	375	14.8	1240	48.8	790	115	S5000/ D4625	S11000/ D10200	10.00	DG09C	20.0	25.2			
13GBB238	A1ABB174	E 14.00R20 S	18	S161/ D158	J	TL	GL073A	375	14.8	1240	48.8	690	100	S4625/ D4250	S10200/ D9370	10.00		20.0	25.2			
13GBB239	A1ABB175	E 14.00R20 S	20	S164/ D161	G	TL	GL073A	375	14.8	1240	48.8	790	115	S5000/ D4625	S11000/ D10200	10.00		20.0	25.2			
13GBB293	A1ABB214	E 16.00R20 S	18	173	G	TL	GL073A	438	17.2	1309	51.5	790	115	6500	14350	11.25		20.0	25.2			
TBA	A1ABB422	335/80R20	16	149	K	TL	GL073A	335	13.2	1040	40.9	660	95	3250	7160	9.00		18.0	22.7			
13GBB121	A1ABB093	395/85R20	14	158	G	TL	GL073A	396	15.6	1219	48.0	660	95	4250	9370	10.00		25.0	31.5			
TBA	TBA	395/85R20	16	162	J	TL	GL073A	396	15.6	1219	48.0	790	115	4750	10470	10.00		25.0	31.5			
TBA	A1ABB322	395/85R20	20	164	G	TL	GL073A	396	15.6	1219	48.0	830	120	5000	11000	10.00		25.0	31.5			
TBA	TBA	15.5R20	18	170	G	TL	GL073A	440	17.3	1270	50.0	790	115	6000	13230	11.25		15.0	18.9			
TBA	11ABB282	15.5R20	20	173	G	TL	GL073A	440	17.3	1270	50.0	900	130	6500	14350	11.25		15.0	18.9			

2013前进外贸轮胎-内页-ok.indd 62 2013-9-17 17:09:05

Radial OTR Tyre Contents

Uses and Characteristics 64
TRA Classification 65
Tread Designs and Application 66-68
Tread Pattern 69
Technical Data 70-71

2013前进外贸轮胎-内页-ok.indd 63 2013-9-17 17:09:05

OFF-THE-ROAD TYRES

USES AND CHARACTERISTICS OF OFF-THE-ROAD TYRES

The qualities which off-the-road tyres must possess differ somewhat according to the function they must serve and the type of vehicles on which they are mounted.

These differences are outlined in Table.

Table 1

Type	Function	Vehicles	Main characteristics required
Earthmover	Transporting		Cut-resistance Wear-resistance Heat-resistance Shock burst-resistance
Load and dozer	Loading and dozing		Cut-resistance Wear-resistance
Grader	Grading ,leveling		Traction Maneuverability(directioal stability)
High-speed vehicle	High-speed transpoting		Heat-resistance Wear-resistance Traction
Industrial	Handling		Wear-resistance Impact and Puncture resistance Heat-resistance

2013前进外贸轮胎-内页-ok.indd 64 2013-9-17 17:09:06

TRA Classification and Corresponding Advance Off-The-Road TYRES

Off-The-Road tyres are classified by the TRA as follows, and the names of the tread patterns of the corresponding Advance Off-The-Road tyres are described below:

TRA Classification	Tread Type	Advance Radial Tread Pattern
E=Earthmover		
E-2	Traction	GL982 GL904
E-3	Rock	GL912 GL901 GL902 GL906
E-4	Rock Deep	GL906
G=Grader		
G-1	Rib	
G-2	Traction	GL982 GL903
G-3	Rock	
G-4	Rock Deep	
L=Loader & Dozer		
L-2	Traction	GL903
L-3	Rock	GL902
L-4	Rock Deep	
L-5	Rock Extra-Deep	
L-5S	Smooth Extra-Deep	
Mobile Crane Service (High-Speed)		
Mobile Crane		GL904 GL905
Industrial Service		
IND-3		GL902
IND-4		GL906 GL907

2013前进外贸轮胎-内页-ok.indd 65 2013-9-17 17:09:06

Tread Designs and Application

Earthmover Service

E-2

GL982

Size	Type
14.00R24	TT/TL

E-3

GL912

Size	Type
14.00R24	TT
13.00R25	TT/TL
14.00R25	TT

GL901

Size	Type
18.00R25	TT/TL

GL902

Size	Type
20.5R25	TL
23.5R25	TT/TL
26.5R25	TL
29.5R25	TL

GL902+

Size	Type
23.5R25	TT/TL

GL906

Size	Type
650/65R25	TL

E-4

GL906

Size	Type
29.5R25	TL

RADIAL OTR TYRES

2013前进外贸轮胎-内页-ok.indd 66 2013-9-17 17:09:07

Grader Service

G-2

GL982

Size	Type
13.00R24TG	TL
14.00R24	TT/TL

GL903

Size	Type
17.5R25	TT/TL

Loader & Dozer Service

L-2

GL903

Size	Type
17.5R25	TT/TL

L-3

GL902

Size	Type
20.5R25	TT/TL
23.5R25	TT/TL
26.5R25	TL
29.5R25	TL

GL902+

Size	Type
23.5R25	TT/TL

2013前进外贸轮胎-内页-ok.indd 67 2013-9-17 17:09:07

Mobile Crane Service (High-Speed)

GL904

Size	Type
385/95R24	TT/TL
385/95R25	TL

GL905

Size	Type
445/95R25	TT/TL

Industrial Service

IND-3

GL902

Size	Type
20.5R25	TL
23.5R25	TL
26.5R25	TL
29.5R25	TL

IND-4

GL906

Size	Type
29.5R25	TL

GL907

Size	Type
12.00R24	TT/TL
14.00R24	TT/TL
18.00R25	TT/TL

2013前进外贸轮胎-内页-ok.indd 68 2013-9-17 17:09:09

Tread Pattern of Advance Radial OTR

GL901

GL902

GL902+

GL903

GL904

GL905

GL906

GL907

GL912

GL982

RADIAL OTR TYRES

2013前进外贸轮胎-内页-ok.indd 69 2013-9-17 17:09:12

TECHNICAL DATA

Part No.	ERP No.	Tyre Size	Ply Rating	Compound Code	Load Index	Speed Symbol	Type	Pattern	Overall Width (mm)	Overall Width (in.)	Overall Diameter (mm)	Overall Diameter (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth (mm)	Tread Depth (32nds)
EARTHMOVERS																				
13GBB241	A1ABB177	14.00R24	☆☆		168	B	TL	GL982 (E-2)	376	14.8	1360	53.5	700	102	5600	12300	10.00	TL	28.5	35.9
13GBB750	11ABB426	14.00R24	☆☆		168	B	TT	GL982 (E-2)	376	14.8	1360	53.5	700	102	5600	12300	10.00	DG09C	28.5	35.9
13GBB761	11ABB437	14.00R24	☆☆☆		169	B	TT	GL912(E-3)	370	14.6	1365	53.7	700	100	5800	127900	10.00	DG09C	26.5	33.4
13GBB763	11ABB439	13.00R25	☆☆☆		163	B	TL	GL912(E-3)	325	12.8	1305	51.4	700	100	4875	10700	8.50	TL	26.0	32.8
13GBB764	11ABB440	13.00R25	☆☆☆		163	B	TT	GL912(E-3)	325	12.8	1305	51.4	700	100	4875	10700	8.50	DG09C	26.0	32.8
13GBB765	11ABB441	14.00R25	☆☆☆		169	B	TT	GL912(E-3)	385	15.2	1365	53.7	900	130	5800	12790	10.00	DG09C	20.5	25.8
13GBB405	A1ABB279	18.00R25	☆☆	1S	185	B	TL	GL901 (E-3)	505	19.9	1622	63.9	700	102	9250	20400	13.00	TL	34.5	43.5
13GBB412	A1ABB287	18.00R25	☆☆	1S	185	B	TT	GL901 (E-3)	505	19.9	1622	63.9	700	102	9250	20400	13.00	DG09C	34.5	43.5
13GBB404	A1ABB278	23.5R25	☆☆	1S	185	B	TL	GL902+(E-3)	622	24.5	1637	64.4	525	76	9250	20400	19.50	TL	41.0	51.7
13GBB319	A1ABB240	23.5R25	☆☆	1S	185	B	TT	GL902+(E-3)	622	24.5	1637	64.4	525	76	9250	20400	19.50	TT	41.0	51.7
13GBB665	A1ABB425	23.5R25	☆☆	1S	185	B	TL	GL902(E-3)	610	24.0	1588	62.5	525	76	9250	20400	19.50	TL	41.0	51.7
13GBB667	A1ABB427	23.5R25	☆☆	1S	185	B	TT	GL902(E-3)	610	24.0	1588	62.5	525	76	9250	20400	19.50	TT	41.0	51.7
13GBB312	A1ABB276	26.5R25	☆☆	1S	193	B	TL	GL902(E-3)	675	26.6	1755	69.1	525	76	11500	25400	22.00	TL	45.5	57.3
13GBB194	A1ABB132	29.5R25	☆☆	1S	200	B	TL	GL902(E-3)	770	30.3	1880	74.0	525	76	14000	30900	25.00	TL	50.0	63.0
13GBB285	11ABB242	29.5R25	☆☆	1S	200	B	TL	GL906(E-4)	770	30.3	1921	75.6	525	76	14000	30900	25.00	TL	57.0	71.8
13GBB283	11ABB112	18.00R25	☆☆	2S	185	B	TL	GL901 (E-3)	505	19.9	1622	63.9	700	102	9250	20400	13.00	TL	34.5	43.5
13GBB414	A1ABB289	18.00R25	☆☆	2S	185	B	TT	GL901 (E-3)	505	19.9	1622	63.9	700	102	9250	20400	13.00	DG09C	34.5	43.5
13GBB320	A1ABB241	23.5R25	☆☆	2S	185	B	TL	GL902+(E-3)	622	24.5	1637	64.4	525	76	9250	20400	19.50	TL	41.0	51.7
13GBB321	A1ABB242	23.5R25	☆☆	2S	185	B	TT	GL902+(E-3)	622	24.5	1637	64.4	525	76	9250	20400	19.50	TT	41.0	51.7
13GBB511	11ABB299	20.5R25	☆☆	2S	177	B	TL	GL902(E-3)	532	20.9	1482	58.3	525	76	7300	16090	17.00	TL	33.0	41.6
13GBB666	A1ABB426	23.5R25	☆☆	2S	185	B	TL	GL902(E-3)	610	24.0	1588	62.5	525	76	9250	20400	19.50	TL	41.0	51.7
13GBB668	A1ABB428	23.5R25	☆☆	2S	185	B	TT	GL902(E-3)	610	24.0	1588	62.5	525	76	9250	20400	19.50	TT	41.0	51.7
13GBB313	A1ABB277	26.5R25	☆☆	2S	193	B	TL	GL902(E-3)	675	26.6	1755	69.1	525	76	11500	25400	22.00	TL	45.5	57.3
13GBB195	A1ABB133	29.5R25	☆☆	2S	200	B	TL	GL902(E-3)	770	30.3	1880	74.0	525	76	14000	30900	25.00	TL	50.0	63.0
13GBB322	A1ABB243	29.5R25	☆☆	2S	200	B	TL	GL906(E-4)	770	30.3	1921	75.6	525	76	14000	30900	25.00	TL	57.0	71.8
13GBB722	A1ABB481	650/65R25	☆☆	2S	180	B	TL	GL906(E-3)	648	25.5	1480	58.3	425	62	8000	17600	19.50	TL	40.0	50.4
GRADER																				
13GBB747	11ABB399	13.00R24TG	☆	1S	146	A8	TL	GL982 (G-2)	330	13.0	1295	51.0	375	54	3000	6600	8.00	TL	29.0	23.0
13GBB240	A1ABB176	14.00R24	☆		153	A8	TL	GL982 (G-2)	376	14.8	1360	53.5	375	54	3650	8050	10.00	TL	28.5	35.9
13GBB749	11ABB425	14.00R24	☆		153	A8	TT	GL982 (G-2)	376	14.8	1360	53.5	375	54	3650	8050	10.00	DG09C	28.5	35.9
13GBB314	A1ABB235	17.5R25	☆	1S	153	A8	TL	GL903 (G-2)	455	17.9	1360	53.5	300	44	3650	8050	14.00	TL	27.5	34.6
13GBB751	11ABB427	17.5R25	☆	1S	153	A8	TT	GL903 (G-2)	455	17.9	1360	53.5	300	44	3650	8050	14.00	DG09C	27.5	34.6
13GBB315	A1ABB236	17.5R25	☆	2S	153	A8	TL	GL903 (G-2)	455	17.9	1360	53.5	300	44	3650	8050	14.00	TL	27.5	34.6
13GBB752	11ABB428	17.5R25	☆	2S	153	A8	TT	GL903 (G-2)	455	17.9	1360	53.5	300	44	3650	8050	14.00	DG09C	27.5	34.6

2013前进外贸轮胎-内页-ok.indd 70 2013-9-17 17:09:13

Part No.	ERP No.	Tyre Size	Ply Rating	Compound Code	Load Index	Speed Symbol	Type	Pattern	Overall Width (mm)	Overall Width (in.)	Overall Diameter (mm)	Overall Diameter (in.)	Infl. (kPa)	Infl. (psi)	Max. Load (kg)	Max. Load (lbs.)	Design Rim Width	Tyre Valve	Tread Depth（mm）	Tread Depth（32nds）
LOADERS																				
13GBB316	A1ABB237	17.5R25	☆	2S	176	A2	TL	GL903 (L-2)	455	17.9	1360	53.5	500	73	7100	15700	14.00/1.5	TL	27.5	34.6
13GBB753	11ABB434	17.5R25	☆	2S	176	A2	TT	GL903 (L-2)	455	17.9	1360	53.5	500	73	7100	15700	14.00/1.5	DG09C	27.5	34.6
13GBB317	A1ABB238	23.5R25	☆	2S	195	A2	TL	GL902+ (L-3)	622	24.5	1637	64.4	500	73	12150	26800	19.5	TL	41.0	51.7
13GBB282	11ABB243	23.5R25	☆	2S	195	A2	TT	GL902 +(L-3)	622	24.5	1637	64.4	500	73	12150	26800	19.5	DG09C	41.0	51.7
13GBB454	A1ABB309	20.5R25	☆	2S	186	A2	TL	GL902 (L-3)	532	20.9	1482	58.3	500	73	9500	20900	17.00	TL	33.0	41.6
13GBB755	11ABB430	20.5R25	☆	2S	186	A2	TT	GL902 (L-3)	532	20.9	1482	58.3	500	73	9500	20900	17.00	DG09C	33.0	41.6
13GBB663	A1ABB423	23.5R25	☆	2S	195	A2	TL	GL902 (L-3)	610	24.0	1588	62.5	500	73	12150	26800	19.5	TL	41.0	51.7
13GBB664	A1ABB424	23.5R25	☆	2S	195	A2	TT	GL902 (L-3)	610	24.0	1588	62.5	500	73	12150	26800	19.5	DG09C	41.0	51.7
13GBB403	A1ABB274	26.5R25	☆	2S	202	A2	TL	GL902 (L-3)	675	26.6	1755	69.1	500	73	15000	33100	22.00	TL	45.5	57.3
13GBB417	A1ABB292	26.5R25	☆	3S	202	A2	TL	GL902 (L-3)	675	26.6	1755	69.1	500	73	15000	33100	22.00	TL	45.5	57.3
13GBB284	11ABB113	29.5R25	☆	2S	208	A2	TL	GL902(L-3)	770	30.3	1880	74.0	500	73	18000	38700	25.00	TL	50.0	63.0
13GBB409	11ABB249	29.5R25	☆	3S	208	A2	TL	GL902(L-3)	770	30.3	1880	74.0	500	73	18000	38700	25.00	TL	50.0	63.0
HIGH-SPEEED VEHICLES																				
13GBB387	A1ABB296	385/95R24 (14.00R24)	☆☆☆		170	E	TL	GL904 (E-2)	385	15.2	1365	53.7	900	131	6000	13200	10.00	TL	20.5	25.8
13GBB748	11ABB424	385/95R24 (14.00R24)	☆☆☆		170	E	TT	GL904 (E-2)	385	15.2	1365	53.7	900	131	6000	13200	10.00	DG09C	20.5	25.8
13GBB386	A1ABB295	385/95R25 (14.00R25)	☆☆☆		170	E	TL	GL904(E-2)	385	15.2	1365	53.7	900	131	6000	13200	10.00	TL	20.5	25.8
13GBB384	A1ABB257	445/95R25	☆☆		174	F	TL	GL905	436	17.2	1480	58.3	900	131	6700	14770	11.25	TL	25.5	32.1
13GBB759	11ABB435	445/95R25	☆☆		174	F	TT	GL905	436	17.2	1480	58.3	900	131	6700	14770	11.25	DG09C	25.5	32.1
INDUSTRIAL SERVICE , IND-3																				
13GBB483	11ABB288	20.5R25	☆☆☆		193	A5	TL	GL902	532	20.9	1482	58.3	650	94	11500	25400	17.00/2.0	TL	33.0	26.2
13GBB368	A1ABB261	23.5R25	☆☆☆		208	A5	TL	GL902	610	24.0	1588	62.5	780	113	18000	38700	19.50	TL	41.0	51.7
13GBB433	A1ABB299	26.5R25	☆☆☆		217	A5	TL	GL902	675	26.6	1755	69.1	780	113	23000	50700	22.00	TL	45.5	57.3
13GBB515	11ABB303	29.5R25	☆☆☆		224	A5	TL	GL902	777	30.6	1881	74.1	780	113	28000	61500	25.00	TL	50.0	63.0
INDUSTRIAL SERVICE , IND-4																				
TBA	11ABB397	12.00R24	☆☆☆		178	A5	TL	GL907	305	12.0	1225	48.2	1000	145	7500	16530	8.50	TL	39.0	49.1
TBA	11ABB396	12.00R24	☆☆☆		178	A5	TT	GL907	305	12.0	1225	48.2	1000	145	7500	16530	8.50	DG09C	39.0	49.1
13GBB534	A1ABB356	14.00R24	☆☆☆		193	A5	TT	GL907	382	15.0	1413	55.6	1000	145	11500	25360	10.00	DG09C	63.0	79.4
TBA	11ABB447	14.00R24	☆☆☆		193	A5	TL	GL907	382	15.0	1413	55.6	1000	145	11500	25360	10.00	TL	63.0	79.4
13GBB754	11ABB429	18.00R25	☆☆☆		207	A5	TT	GL907	508	20.0	1655	65.2	1000	145	17500	38600	13.00	DG09C	34.5	43.5
13GBB431	A1ABB297	18.00R25	☆☆☆		207	A5	TL	GL907	508	20.0	1655	65.2	1000	145	17500	38600	13.00	TL	34.5	43.5
13GBB757	11ABB432	29.5R25	☆☆☆		224	A5	TL	GL906	768	30.2	1803	71.0	780	113	28000	61500	25.00	TL	57.0	71.8

NOTE:
1) Speed Symbol: G - 90km/h
F - 80 km/h
E - 70 km/h
B - 50 km/h
A2 - 10 km/h

2) Compound Code: 1S - Standard
2S - Cut-Resistant
3S - Heat-Resistant

2013前进外贸轮胎-内页-ok.indd 71 2013-9-17 17:09:13

FLATPROOF TYRES

The Structure of flatproof tyres

Performance of Flatproof tyres

Even if tyres are driving in the most abominable and dangerous conditions,the vehicles equipped with flatproof tyres can roll over acute-objects such as scrap irons nails,rocks etc.Indeed the tyres even when shot by automatic rifle AK47 also can move on.

- **Vehicles of Military Forces**
- **Vehicles for Other Special Applications**
- **Vehicles of Mining Industry**

Safety	● Avoiding the danger of lost control because of sudden tyre flat. ● Stable driving in the conditions of tough road and overload. ● Enhancing the vehicle's stability which enables to remain. moving even if the tyre flat.
Economical	● Increasing the Performance life by one to two times as.compared with pneumatic tyres. ● Improving the efficiency. ● Decreasing Largely the maintenance cost.
Excellent Capabiliey	● Prolonged performance life due to excellent heart resistance. ● Best quality assurance.
Universality	● All of the pneumatic tyres can be changed to the run flat tyres ● Tyres design according to the client's request ● Flatproof tyres of "ADVANCE" brand in confor mity with Chinese Standard,TRA,ETRTO and JATMA.

Features of Flatproof Tyres

- Driving comfortablely-decreasing the tiredness of driving and improving the efficiently of driving.
- Characterized by excellent damping property-preventing equipment from injure by shaking
- Stable driving property-supporting greater load improving stability, increasing traction.
- Avoiding the risk of air leak and blowing out.
- Wider contact area,chara cterized by big traction in soft and muddy road service.
- Good endurance,all-weateher property,unaffected by extreme temperature.
- Reducing cost in maintenance-reducing tyre rupture and expansion of blot hole,driving comfortably,as pneumatic tyre hardness value 8
- Economical-Saving cost in maintenance and downtime.

2013前进外贸轮胎-内页-ok.indd 72 2013-9-17 17:09:14